



Liquidtight Flexible Steel Conduit CSA Certified

TYPE - CSA




[Contact your local Sales Representative](#)
[Click Here for Printable Version](#)


| Trade Size | Metric Trade Size | Type | Inside Bend Radius | Wt. (Lbs.)/100 Ft. | Carton Length | Footage Part # | Reel Length | Footage Part # | Price Per 100 FT |
|------------|-------------------|----------|--------------------|--------------------|---------------|----------------|-------------|----------------|------------------|
| 3/8" | 12 | CSA -10 | 2.0" | 25 | 100 | 70101 | 500 | 70103 | \$310.00 |
| 1/2" | 16 | CSA -11 | 3.0" | 35 | 100 | 71101 | 500 | 71103 | \$358.00 |
| 3/4" | 21 | CSA -12 | 4.0" | 52 | 100 | 72101 | 500 | 72104 | \$493.00 |
| 1" | 27 | CSA -13 | 5.0" | 59 | 100 | 73102 | 400 | 73104 | \$683.00 |
| 1-1/4" | 35 | CSA -14 | 6.2" | 86 | 50 | 74102 | 200 | 74104 | \$1,026.00 |
| 1-1/2" | 41 | CSA -15 | 4.5" | 122 | 50 | 75102 | 150 | 75104 | \$1,384.00 |
| 2" | 53 | CSA -16 | 6.0" | 154 | 50 | 76102 | 100 | 76104 | \$1,764.00 |
| 2-1/2" | 63 | CSA -17 | 8.0" | 204 | 25 | 77102 | - | - | \$3,046.00 |
| 3" | 78 | CSA -18 | 10.0" | 264 | 25 | 78102 | - | - | \$4,250.00 |
| 3-1/2" | 91 | CSA -350 | - | - | - | - | - | - | \$5,196.00 |
| 4" | 103 | CSA -19 | 12.0" | 368 | 25 | 79102 | - | - | \$6,012.00 |

SIZES: 1-1/2" - 4"

Sizes 3/8" - 1-1/4"



Squarelock with Filler



Interlock

See [Chart for Dimensions and Tolerances.](#)

TYPE - CSA

This flexible liquidtight steel conduit is certified by the Canadian Standards Association. Its design and function is similar to that of type LA, except that it cannot be used as a ground return path per the Canadian code, and it offers a wider operating temperature range.

CONSTRUCTION:

The flexible inner core is made from a spiral wound strip of heavy-gauge, corrosion-resistant, hot-dipped galvanized steel. The 3/8 through 1-1/4 inch trade sizes are cord-packed.

The durable PVC flame-retardant jacket is designed for good flexibility and impact resistant characteristics at low temperatures.

APPLICATION:

This conduit is intended for use according to the Canadian Electrical Code as described in clause 12-1300 for dry, damp or wet locations and in hazardous areas where flexibility is necessary per 18-202(4)(b) and 18-302(4) for both Class II and Class III locations.

 Certified File #LL18858. Conforms to CSA Standard C22.2 No 56. Flame Test Rating FT-4 per CSA Standard C22.2 No 0.3.



[WEEE and RoHS Compliant](#)

 BS EN IEC 61386 Classification Code 445240650414

ARRA:

For ARRA Certification Letter, please [click here](#)

STANDARD COLORS:

Black

WORKING TEMPERATURES:

-40°C to 75°C

Flexibility: [See the Flexibility Comparison Guide](#)

Metal Used: Steel

Plastic Used: PVC [See the Chemical Resistance Guide](#)

| High Mech. Strength | Listed For Direct Burial | Halogen Free | Low Fire Hazard | Accepts Standard Liquidtight Fittings | Self Extinguish | EMI/RFI Shielding | Oil Resistance | Acid Resistance |
|---------------------|--------------------------|--------------|-----------------|---------------------------------------|-----------------|-------------------|----------------|-----------------|
| X | | | | X | X | | X | X |

[Packaging, Disclaimer and Warranty](#)

® Electri-Flex Company 1-800-323-6174

[Privacy](#) [Terms](#)

