

MULTICONDUCTOR CABLE

MULTICONDUCTOR FOIL SHIELD

300V - 22 GAUGE



Description:

Each Conductor Stranded Tinned Copper, Color Coded Polyvinylchloride (UL Style 1061) Insulated. Overall Aluminum/Polyester Shield with Stranded Tinned Copper Drain Wire, Nylon Rip Cord for Ease of Jacket Stripping, Gray PVC Jacket Overall.

Specifications:

UL Listed, NEC Type CM, 75°C
 UL AWM Style 2464, 80°C, 300V
 CSA Certified PCC FT-4
 OSHA Acceptable

WEICO NO.	NO. OF CONDUCTORS	NOM. JACKET THICKNESS (INCHES)	NOM. O.D. (IN)
#22 AWG (7/30) Nom. Ins. Thickness .010"			
7602	2	.032	.180
7603	3	.032	.190
7604	4	.032	.210
7606	6	.032	.230
7608	8	.032	.260
7610	10	.032	.280
7615	15	.032	.320
7620	20	.032	.350
7625	25	.032	.380
7630	30	.032	.410

WEICO NO.	NO. OF CONDUCTORS	NOM. JACKET THICKNESS (INCHES)	NOM. O.D. (IN)
7640	40	.032	.460
7650	50	.032	.500
7660	60	.032	.540
7670	70	.053	.620
7680	80	.053	.650
7690	90	.053	.690
7600	100	.053	.720

Standard Put-Ups: 100 ft., 500 ft., 1000 ft.