



PRODUCT DATA SHEET

1530 Shields Drive
Waukegan, IL 60185
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 22157
DESCRIPTION: 14/5 STRANDED TYPE SJTOW FILLERLESS FLEXIBLE POWER CABLE
CONSTRUCTION: This cable consists of five bare copper PVC insulated conductors twisted without fillers and an overall PVC jacket.
APPROVALS: UL Standard 62, NEC Article 400, CSA No. 22.2 No. 49
APPLICATION: 300V Portable Outdoor Oil Resistant Flexible Power Cable

Construction Parameters:

Conductor	14 AWG Bare Copper
Stranding	41/30
Insulation Material	PVC
Insulation Thickness	0.031" Nom.
Insulated Conductor Diameter	0.136" Nom.
Number of Conductors	5
Lay Length	4.50" Nom.
Filler Type	Fillerless
Separator/Wrap	Paper Tissue
Jacket Material	PVC
Jacket Thickness	0.032" Nom.
Overall Cable Diameter	0.431" Nom.
Approximate Cable Weight	126.3 Lbs/1M' Nom.
Flame Rating	UL/CSA Horizontal Flame Test

Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300V Max
DC Resistance per Conductor @ 20°C	2.53 Ohms/1M'

Insulation Colors	Black White Red Green Orange
Jacket Color	Black

Legend (Indent Print)	E54864 14-5 SJTOOW (UL) 300V CSA LL39753 14-5 SJTOW 60C FT1
-----------------------	---

The customer will accept all mil lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.