

For more Information
please call

1-800-Belden1



General Description:

18 AWG solid .040" bare copper conductor, gas-injected foam polyethylene insulation, Duobond® + aluminum braid shield (77% coverage), PVC jacket.

Usage (Overall)

Suitable Applications: HDTV, DBS, Broadband CATV, Cable Modem

Physical Characteristics (Overall)

Conductor

AWG:

| # Coax | AWG | Stranding | Conductor Material | Dia. (in.) |
|--------|-----|-----------|--------------------|------------|
| 1 | 18 | Solid | BC - Bare Copper | .040 |

Total Number of Conductors: 1

Insulation

Insulation Material:

| Insulation Material | Dia. (in.) |
|--------------------------------------|------------|
| Gas-injected FPE - Foam Polyethylene | .180 |

Outer Shield

Outer Shield Material:

| Layer # | Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|---------|-------------------------|-------|---|--------------|
| 1 | Bonded Duofoil® | Tape | Bonded Aluminum Foil-Polyester Tape-Aluminum Foil | 100 |
| 2 | | Braid | AL - Aluminum | 77 |
| 3 | | Tape | Bonded Aluminum Foil-Polyester Tape w/Shorting Fold | 100 |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Overall Cable

Overall Nominal Diameter: 0.275 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +80°C

UL Temperature Rating: 80°C

Bulk Cable Weight: 32 lbs/1000 ft.

Max. Recommended Pulling Tension: 91 lbs.

Min. Bend Radius/Minor Axis: 2.750 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CATV, CM

CEC/C(UL) Specification: CM

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Series Type: Series 6

Flame Test

UL Flame Test: UL1685 UL Loading

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
75.000

Nom. Inductance:

Inductance (µH/ft)
.097

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
16.2

Nominal Velocity of Propagation:

VP (%)
83

Nominal Delay:

Delay (ns/ft)
1.2

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
6.4

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
4.6

Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 5 | 0.5 |
| 55 | 1.4 |
| 211 | 2.6 |
| 500 | 4.1 |
| 750 | 5.1 |
| 862 | 5.5 |
| 1000 | 6.0 |
| 1450 | 7.8 |
| 1800 | 8.6 |
| 2250 | 9.8 |
| 3000 | 11.3 |

Max. Attenuation:

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 5 | 0.67 |
| 55 | 1.60 |
| 211 | 2.87 |
| 500 | 4.48 |
| 750 | 5.59 |
| 862 | 5.98 |
| 1000 | 6.54 |
| 1450 | 8.0 |
| 1800 | 8.8 |
| 2250 | 10.0 |
| 3000 | 11.9 |

Max. Operating Voltage - UL:

Voltage
350 V RMS

Shield Effectiveness:

| Start Freq. (MHz) | Stop Freq. (MHz) | Effectiveness (dB) |
|-------------------|------------------|--------------------|
| 5 | 50 | 105 |
| 50 | 1000 | 125 |

Minimum Structural Return Loss:

| Start Freq. (MHz) | Stop Freq. (MHz) | Min. SRL (dB) |
|-------------------|------------------|---------------|
| 5 | 1000 | 20 |
| 1000 | 2250 | 15 |
| 2250 | 3000 | 10 |

Sweep Test

Sweep Testing: 5 MHz - 3 GHz

Notes (Overall)

Notes: Shielding effectiveness determined from screening attenuation measurement when tested in accordance with IEC 61196-1.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|----------|-------------|-------|-------|----------------------------|
| 7915A 009U1000 | 1,000 FT | 30.000 LB | WHITE | | #18 GIFHDLDPPE SH FS PVC |
| 7915A 009U500 | 500 FT | 15.500 LB | WHITE | | #18 GIFHDLDPPE SH FS FRPVC |
| 7915A 009I000 | 1,000 FT | 30.000 LB | WHITE | C | #18 GIFHDLDPPE SH FS FRPVC |
| 7915A 009500 | 500 FT | 15.500 LB | WHITE | C | #18 GIFHDLDPPE SH FS FRPVC |
| 7915A 010N1000 | 1,000 FT | 31.000 LB | BLACK | | #18 GIFHDLDPPE SH FS FRPVC |
| 7915A 010U1000 | 1,000 FT | 30.000 LB | BLACK | | #18 GIFHDLDPPE SH FS PVC |
| 7915A 010U500 | 500 FT | 15.500 LB | BLACK | | #18 GIFHDLDPPE SH FS FRPVC |
| 7915A 010I000 | 1,000 FT | 30.000 LB | BLACK | C | #18 GIFHDLDPPE SH FS FRPVC |
| 7915A 010500 | 500 FT | 15.500 LB | BLACK | C | #18 GIFHDLDPPE SH FS FRPVC |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 4 Revision Date: 08-10-2012

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.