

Heyco® PCB Supports Selection Guide

Imperial Spacing Lengths

PCB Mounting Hole Diameter		CHASSIS				MOUNTING STYLES		SERIES	PAGE
in.	mm.	Maximum Thickness		Mounting Hole Diameter		PCB End	Chassis End		
		in.	mm.	in.	mm.				

Flat Rest Mounts

.000	0,0	.062	1,6	.098	2,5	flat rest mount	teardrop snap lock	HPS-TD	7-11
		.078	2,0	.125	3,2	flat rest mount	arrowhead snap lock	HMPS	7-11
				.187	4,8	flat rest mount	arrowhead snap lock	HPS	7-9

For PCB's up to .062" (1,6 mm) Thick

.098	2,5	.039	1,0	.079	2,0	teardrop snap lock	teardrop snap lock	HSP-MDL-3	7-11
		.062	1,6	.098	2,5	teardrop snap lock	teardrop snap lock	HDLSPTH	7-4
				cupped teardrop lock	cupped teardrop lock	HCDLCBST	7-9		
				.125	3,2	bayonet snap lock 8,7	teardrop snap lock	HTLSP	7-7
.125	3,2	.062	1,6	.125	3,2	two prong snap lock	two prong snap lock	HMSPDLN	7-10
						two prong snap fit	two prong snap lock	HMCBP	7-10
						bayonet snap lock 8,7	two prong snap lock	HLSP11	7-7
						bayonet snap lock 8,7	arrowhead snap lock	HLSP9	7-7
.152	3,9	.062	1,6	.125	3,2	two prong snap lock	two prong snap lock	HMSPDL	7-10
						two prong snap fit	two prong snap lock	HCBP	7-10
.157	4,0	.055	1,4	.188	4,8	bayonet snap lock 10,2	arrowhead snap lock	HLSP8	7-6
						flanged two prong snap lock	flanged two prong snap lock	HMSPS	7-11
		.062	1,6	.157	4,0	two prong snap lock	two prong snap lock	HSP1	7-4
						two prong snap lock	two prong snap lock	HSP3	7-4
						arrowhead snap lock	arrowhead snap lock	HSSL	7-9
		.070	1,8	.187	4,8	arrowhead snap lock	arrowhead snap lock	HLSP4	7-5
						bayonet snap fit 10,2	arrowhead snap lock	HLSP1	7-5
						bayonet snap lock 10,2	arrowhead snap lock	HLSP7	7-6
						bayonet snap lock 10,2	winged two prong snap lock	HLSP10	7-7
		.141	3,6	.187	4,8	bayonet snap lock 10,2	winged two prong snap lock	HLSP5	7-6
bayonet snap lock 10,2	arrowhead snap lock					HLSP2	7-5		
.187	4,8	.062	1,6	.187	4,8	two prong snap lock	two prong snap lock	HSP2	7-4

For PCB's up to .078" (2,0 mm) Thick

.125	3,2	.078	2,0	.125	3,2	arrowhead snap lock	arrowhead snap lock	HDLSP4	7-8
.157	4,0	.078	2,0	.157	4,0	arrowhead snap lock	arrowhead snap lock	HDLSP5	7-8
				.187	4,8	arrowhead snap lock	arrowhead snap lock	HDLSP7	7-8
.187	4,8	.078	2,0	.187	4,8	arrowhead snap lock	arrowhead snap lock	HDLSP6	7-8
						bayonet snap lock 15,2	arrowhead snap lock	HLNCBS	7-9

For PCB's up to .090" (2,3 mm) Thick

.157	4,0	.078	2,0	.187	4,8	bayonet snap lock 10,9	arrowhead snap lock	HLSP3	7-5
		.141	3,6	.187	4,8	bayonet snap lock 10,9	arrowhead snap lock	HLSP6	7-6

NEW!

Metric Spacing Lengths

PCB Mounting Hole Diameter		CHASSIS				MOUNTING STYLES		SERIES	PAGE
in.	mm.	Maximum Thickness		Mounting Hole Diameter		PCB End	Chassis End		
		in.	mm.	in.	mm.				

For PCB's up to .062" (1,6 mm) Thick

.098	2,5	.062	1,6	.098	2,5	teardrop snap lock	two prong snap lock	HSP-MDL-AH-1	7-13
		.141	3,6	.098	2,5	teardrop snap lock	teardrop snap lock	HSP-MDL-1	7-12
.138	3,5	.062	1,6	.138	3,5	teardrop snap lock	teardrop snap lock	HSP-MDLS-1	7-12
		.141	3,6	.138	3,5	teardrop snap lock	teardrop snap lock	HSP-MDLS-2	7-12
.157	4,0	.062	1,6	.157	4,0	wingless arrowhead	wingless arrowhead	HDLSP1	7-13
				.187	4,8	wingless arrowhead	wingless arrowhead	HDLSP3	7-13
.187	4,8	.062	1,6	.187	4,8	wingless arrowhead	wingless arrowhead	HDLSP2	7-13