

Screw and Lock Supports - continued

PCB Mounting Hole Diameter		PART DATA				MOUNTING STYLES		SPACING	SERIES	PAGE
in.	mm.	Thread Depth		Mounting Screw		PCB End	Chassis End			
For PCB's up to .062" (1,6 mm) Thick										
.157	4,0	varies †			M4	bayonet snap fit 10,2	female thread #M4	Imperial	HCBS-TF-M4	Consult Heyco
		varies †			6-32	bayonet snap lock 10,2	female thread 6-32	Imperial	HLCBS-TF-632	7-22
						bayonet snap fit 10,2	female thread 6-32	Imperial	HCBS-TF-632	7-22
PCB Thickness Varies										
.157	4,0	varies †			M3	bayonet snap lock 9,5	female thread M3	Metric	HTCBS-M3-6	Consult Heyco
					M4	bayonet snap lock 9,5	female thread M4		HTCBS-M3-8	
								HTCBS-M4-8		

†Thread Depth varies with length of part.

Threaded Male Supports

PCB Mounting Hole Diameter		CHASSIS				MOUNTING STYLES		SPACING	SERIES	PAGE
in.	mm.	Part Thread Length		Mounting Hole Diameter		PCB End	Chassis End			
For PCB's up to .062" (1,6 mm) Thick										
.098	2,5	.250	6,4		M3	teardrop snap lock	male thread M3	Imperial	HMSCBST-M3	Consult Heyco
					M4	teardrop snap lock	male thread M4		HMSCBST-M4	
.125	3,2	.250	6,4		M3	bayonet snap lock 8,7	male thread M3	Imperial	HSCBS3	7-23
					M4	bayonet snap lock 8,7	male thread M4		HSCBS4	
				6-32		bayonet snap lock 8,7	male thread 6-32		HSCBS5	
.152	3,9	.236	6,0		M3	two prong snap fit	male thread M3	Imperial	HSCBS1-M3	7-25
					M4	two prong snap fit	male thread M4		HSCBS1-M4	
				6-32		two prong snap fit	male thread 6-32		HSCBS1-632	
.157	4,0	.250	6,4		M4	bayonet snap lock 10,2	male thread M4	Imperial	HSCBS	7-24
					8-32	bayonet snap lock 10,2	male thread 8-32		HSCBS8	
		.300	7,6		M4	bayonet snap lock 10,2	male thread M4	Imperial	HSCBS7	7-24
				6-32		bayonet snap lock 10,2	male thread 6-32		HSCBS6	
6-32	.300	7,6	6-32			double threaded male - .30" (7,6 mm) thread length	Imperial	HCBS-TMM	7-25	

Adhesive-Back Mount Supports

PCB Mounting Hole Diameter		CHASSIS				MOUNTING STYLES		SPACING	SERIES	PAGE
in.	mm.	Maximum Thickness		Mounting Hole Diameter		PCB End	Chassis End			
.000	0,0	.00	0,0	.00	0,0	flat rest mount	adhesive-back 12,7 sq	Imperial	HPSBM	Consult Heyco
							adhesive-back 17,8 sq			
.098	2,5	.00	0,0	.00	0,0	teardrop snap lock	adhesive-back 12,7 sq	Imperial	HCBS4	7-26
.125	3,2	.00	0,0	.00	0,0	bayonet snap lock 8,7	adhesive-back 12,7 sq	Imperial	HCBS3	7-26
.157	4,0	.00	0,0	.00	0,0	bayonet snap lock 10,2	adhesive-back 17,8 sq	Imperial	HCBS	7-26
							Metric		HCBS-Metric	7-27
						bayonet snap fit 10,2	adhesive-back 17,8 sq	Imperial	HCBS2	7-26

Rivet Mount and Edge Holding Supports

PCB Mounting Hole Diameter		CHASSIS				MOUNTING STYLES		SPACING	SERIES	PAGE
in.	mm.	Maximum Thickness		Mounting Hole Diameter		PCB End	Chassis End			
Rivet Mount - For PCB's .062" (1,6 mm) thick										
.157	4,0	varies †		.165	4,2	bayonet snap lock 10,2	rivet	Imperial	HRLSP	7-28
Rivet Mount - For PCB's .078" (2,0 mm) thick										
.187	4,8	varies †		.165	4,2	arrowhead snap lock	rivet	Imperial	HSRLAHS	7-28
Edge Holding - For PCB's .062" (1,6 mm) thick										
.157	4,0	varies ††		6-32		edge snap lock	self-tap screw #6	Imperial	HTEHCBS	7-29
		.062	1,6	schematic		edge snap lock	reverse rectangular		HRLHCBS	
		.078	2,0	.187	4,8	edge snap lock	arrowhead snap lock		HEHCBS-7	

†For Panel Thicknesses see Rivet Table on page 7-28. ††Varies with length of screw.

Threaded Hex Supports and Spacers

ALL NEW PRODUCT!

Nylon Male/Female Threaded Hex Supports	male thread	female thread	Both	MFS, MFSM	7-30
Nylon Tapped Hex Spacers	female thread	female thread	Both	HST, HSTM	7-31