


“Stay Connected” with



HEYware

a PennEngineering® Company



HEYClip™ Tension Wire Clips - Vinyl U Style

Adhesive-Back Mount



MAXIMUM BUNDLE DIAMETER A		PART NO. Gray	DESCRIPTION	PACKAGING		OVERALL HEIGHT D*		FOOTPRINT**	
in.	mm.			Std. Pack	Small Pack †	in.	mm.	B x C	
WCUA Series									
.13	3,2	3335	WCUA 125	5000	25	.29	7,4	.75 x .75	19,1 x 19,1
.25	6,4	3336	WCUA 250	5000	25	.47	11,9		
.38	9,5	3337	WCUA 375	5000	25	.59	15,1	1.00 x 1.00	25,4 x 25,4
.50	12,7	3338	WCUA 500	5000	10	.61	15,5		
.56	14,3	3339	WCUA 562	1000	10	.64	16,3		
.75	19,1	3341	WCUA 750	1000	10	.90	22,9		
WCDA Series									
NEW PRODUCT!									
.25	6,4	3821	WCDA 250	5000	25	.40	10,2	.50 x .50	12,7 x 12,7
.50	12,7	3822	WCDA 500	3000	25	.73	18,5	.75 x .75	19,1 x 19,1
.75	19,1	3823	WCDA 750	3000	10	1.02	25,9	1.13 x 1.00	28,7 x 25,4
1.00	25,4	3824	WCDA 1000	1000	10	1.30	33,0	1.50 x 1.25	38,1 x 31,8

Standard color gray.



* At maximum wire capacity.

** Custom lengths available by special order, consult Heyco.

† To order Small Packs, please add the suffix -P to Part No.; e.g., 3335-P.



WCUA



WCDA

Material	PVC
Flammability Rating	94V-0
Temperature Range	-20°F (-29°C) to 150°F (66°C)

Quick
Specs