

# Part Number: 8134FO



# RS232/485 Low Cap, #28-4pr, FPO, O/A Foil, PVC Jkt, CL2, 120 $\Omega$

## **Product Description**

Computer EIA RS-232/485 Cable, 28 AWG stranded (7x36) tinned copper conductors, Datalene® insulation, twisted pairs, overall Beldfoil® shield (100% coverage), 28 AWG stranded tinned copper drain wire, PVC jacket.

### **Technical Specifications**

## **Physical Characteristics (Overall)**

Conduc	ctor		
AWG	Stranding	Material	No. of Pairs
28	7x36	TC - Tinned Copper	4
Condu	ctor Count:		
Condu	ctor Size:		

## Insulation

Material	Material Trade Name	Nominal Wall Thickness
FPE - Foamed Polyethylene	Datalene®	0.015 in

#### Color Chart

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White
3	White/Green & Green/White
4	White/Brown & Brown/White

#### **Outer Shield Material**

Тур	e Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Тар	Aluminum Foil-Polyester Tape	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	28	7x36 mm

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.27 in	0.035 in

### **Electrical Characteristics**

65 Ohm/1000ft 20 Ohm/1000ft	
apacitance	
Nom. Capacitance Conductor to Conductor Nom. Capacitance Conductor to Other Conductor	to Shield
11 pF/ft 20 pF/ft	
Shielding: Foil(s) or Cop	per Tape(s

120 Ohm

Max. Delay Skew Nominal Velocity of Propagation (VP) [%] 78 ns/100m 78 %

Current

## Max. Recommended Current [A]

0.9 Amps per conductor @ 25°C A

Voltage

UL Description	UL Voltage Rating
UL AWM Style 2919	30V RMS (UL AWM Style 2919)
CL2	150V RMS (CL2)

#### **Temperature Range**

Operating Temp Range:	-30°C To +80°C
Mechanical Characteristics	
Bulk Cable Weight:	27 lbs/1000ft
Min Bend Radius/Minor Axis:	2.75 in

NEC/(UL) Specification:	CL2
UL AWM Style:	2919 (30 V 80°C)

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes

#### Flammability, LS0H, Toxicity Testing

_ Flammability:	UL1685 UL Loading

### Plenum/Non-Plenum

Plenum (Y/N):	No	

#### **Part Number**

UL

Variants		
Item #	Color	Footnote
8134FO 0601000	CHROME	С
8134FO 060500	CHROME	С
Footnote:		

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.