

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 821013-

RG-11/U PLENUM COAXIAL CABLE WITH 60% ALUMINUM **DESCRIPTION:**

BRAID

UL LISTED AS CMP/CL2P/CATVP **RATING:**

\/ \/ \ \ | | | | | *

C(UL) LISTED AS CMP FT6

EQUIV. COMMSCOPE 2285K REFERENCE:

Construction Parameters:

		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductors:	14 AWG (1/.064) Solid Copper Clad Steel	<u> </u>	0.064
Dielectric:	Foam FEP color natural	0.108	0.280
Shielding:	Aluminum/Polyester/Aluminum Foil with 60% Aluminum Braid		0.312
Jacket:	Polyvinylidene Fluoride (Kynar®)	0.017	0.346

Electrical Properties:

Cable Cross-section:

(NOT TO SCALE)

		VALUE
Conductor Resistance (o	11.1	
Impedance (ohms):	75	
Capacitance (pF/ft):	16.5	
Velocity of Propagation (82	
Attenuation (db/100 ft):	10 MHz	0.5
	50 MHz	1.1
	100 MHz	1.4
	200 MHz	2.1
	400 MHz	3.3
	700 MHz	5.4
	1000 MHz	5.9
	1450 MHz	7.2
	1800 MHz	7.9
	2200 MHz	9.5



Miscellaneous Information:

Jacket Color: Natural

Jacket Print (Blue): CCI 821013 RG11 14 AWG CCS DUAL SHIELD 60% AL

BRAID E118963-I (UL) TYPE CMP/CL2P/CATVP 125C -

c(UL) CMP FT6 SWEPT TO 3.0 GHZ WO# UL 910 Steiner Tunnel Smoke and Flame Test

Flame Rating: Temperature Rating: 125° C Applicable NEC Article: 725, 800, 820

Approximate Weight (lb/1000 ft): 54

Connector: Corning Gilbert Inc. # GF-11-300P/388

This product complies with European Directive 2002/95/EC (RoHS)

On special orders the customer will accept all factory lengths and ± 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We reserve the right to review and modify all constructions to conform with the latest Regulatory requirement. We disclaim all liability in connection with the use of information contained herein or otherwise. This specification is propriety intellectual property of COLEMAN CABLE. Any information contained herein shall not be disclosed to any party without written consent of COLEMAN CABLE.

Company Name:		
Customer Approval:	 Date:	

09/01/11 Issued:

Nominal value