



PRODUCT DATA SHEET

1586 South Lakeside Drive
Waukegan, IL 60185
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 823225
DESCRIPTION: 18/2 STRANDED TYPE SJOOOW FLEXIBLE POWER CABLE
CONSTRUCTION: This cable consists of two bare copper insulated conductors cabled with fillers and an overall jacket.
APPROVALS: UL Standard 62, CSA 22.2 No. 49, NEC Article 400.
APPLICATION: 300V Portable Oil and Water Resistant Submersible Outdoor Flexible Power Cable

Construction Parameters:

Conductor	18 AWG Bare Copper
Stranding	16/30
Insulation Material	Ethylene Propylene (EP)
Insulation Thickness	0.030" Nom.
Insulated Conductor Diameter	0.106" Nom.
Number of Conductors	2
Lay Length	1.50" Nom.
Filler Type	Paper
Separator/Wrap	Paper Tissue
Jacket Material	CPE (chlorinated polyethylene)
Jacket Thickness	0.030" Nom.
Overall Cable Diameter	0.280" Nom.
Approximate Cable Weight	42.6 Lbs/1M' Nom.
Flame Rating	UL/CSA Horizontal Flame Test

Electrical Properties:

Temperature Rating	-40°C to 90°C
Operating Voltage	300 V RMS Max.
DC Resistance per Conductor @ 20°C	6.49 Ohms/1M' Nom.

Insulation Colors	Black White
Jacket Color	Black

Legend  CCI Royal Brand  18/2 SJOOOW E54864-T (UL)
300V -40C to 90C CSA 223373 FT2 Water Resistant P-7K-254013
MSHA
(White Surface Ink Print - MSHA in indent)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____ Date Signed _____

Customer Approval _____

Specification Issue Date: January 12, 2004