



1586 South Lakeside Drive Waukegan, IL 60185 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER:823228DESCRIPTION:12/2 STRANDED TYPE SJOOW FLEXIBLE POWER CABLECONSTRUCTION:This cable consists of two bare copper insulated conductors cabled with fillers and an overall jacket.APPROVALS:UL Standard 62, CSA 22.2 No. 49, NEC Article 400.APPLICATION:300V Portable Oil and Water Resistant Submersible Outdoor Flexible Power Cable

Construction Parameters:

Conductor Stranding Insulation Material Insulation Thickness Insulated Conductor Diameter Number of Conductors Lay Length Filler Type Separator/Wrap Jacket Material Jacket Thickness Overall Cable Diameter Approximate Cable Weight Flame Rating 12 AWG Bare Copper 65/30 Ethylene Propylene (EP) 0.030" Nom. 0.152" Nom. 2 2.50" Nom. Paper Paper Tissue CPE (chlorinated polyethylene) 0.045" Nom. 0.410" Nom. 104.7 Lbs/1M' Nom. UL/CSA Horizontal Flame Test

Electrical Properties:

Temperature Rating Operating Voltage DC Resistance per Conductor @ 20^oC

Insulation Colors Jacket Color

Legend

1.59 Ohms/1M' Nom.

 -40° C to 90° C

300 V RMS Max.

Black White Black

★ CCI Royal Brand ★★★★ 12/2 SJOOW E54864-T (UL) 300V -40C to 90C CSA 223373 FT2 Water Resistant P-7K-254013 MSHA

(White Surface Ink Print - MSHA in indent)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

	Customer	Name
--	----------	------

____ Date Signed ____

Customer Approval _____

Specification Issue Date: January 14, 2004