



Part Number: 82641

Audio/Control/Instrumentation, (1 pr) 24 AWG (7x32) TC, FEP/LS PVC, Foil Shld, CMP

# **Product Description**

One 24 AWG pair stranded (7x32) tinned copper conductors, twisted pair, Teflon® (FEP) insulation, overall Beldfoil shield (100% coverage), Flamarrest® jacket.

# **Technical Specifications**

# **Physical Characteristics (Overall)**

Condu	ctor		
AWG	Stranding	Material	No. of Pairs
24	7x32	TC - Tinned Copper	1
Condu	ictor Count:		
Total Number of Pairs:			
Condu	Conductor Size:		

#### Insulation

Material	Nominal Wall Thickness	
FEP - Fluorinated Ethylene Propylene	0.006 in	

# Color Chart

Number	Color
1	Black & Red

# Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Таре	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	24	7x32 mm

# Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.106 in	0.014 in

# **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
24.1 Ohm/1000ft	17 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield	
31 pF/ft	59 pF/ft	
Shielding:	Foil(s) or Copper Tape(s	

# Inductance



### Current



#### Voltage



### **Temperature Range**

Operating Temp Range:	0°C To +60°C

### **Mechanical Characteristics**

Bulk Cable Weight:	8 lbs/1000ft
Max Recommended Pulling Tension:	16 lbs
Min Bend Radius/Minor Axis:	1.25 in

### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	СМР
CPR Euroclass:	Eca

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
CSA Flammability:	FT6
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Plenum Number:	88641

### **Part Number**

Non-Plenum Number:	8641

# Variants

Item #	Color	Footnote
82641 8771000	Natural	С
82641 877U1000	Natural	
Footnote:		

# © 2018 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.