



Part Number: 83005

Lead Wire, #22 Str SPC, TFE Ins, AWM 1213 105C TYPE E

Product Description

High Temp Plastic Lead Wire, 22AWG (7x30) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Conductors |
|-------|-------------|--------------------------|-------------------|
| 22 | 7x30 | SCC - Silver-coated Copp | per 1 |
| Condu | ctor Count: | 1 | |
| Condu | ictor Size: | 2 | 22 AWG |

Insulation

| Material | Nominal Diameter | Nominal Wall Thickness |
|---------------------------|------------------|------------------------|
| TFE - Tetrafluoroethylene | 0.049 in | 0.01 in |

Outer Jacket Material

| Material | Nominal Diameter |
|-----------|------------------|
| No Jacket | 0.05 in |

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 15.25 Ohm/1000ft

Current

| Element | Max. Recommended Current [A] |
|---------------------------------------|---|
| Mil-Std-975M Table 3.16 (single wire) | Mil-Std-975M Table 3.16 (single wire): 4.5 amps |

Voltage

| Description | Voltage Rating [V] |
|---------------|-------------------------|
| Mil-W-16878/4 | 600 V RMS Mil-W-16878/4 |

Temperature Range

| UL Temp Rating: | 105°C |
|-----------------------|-----------------|
| Operating Temp Range: | -70°C To +200°C |

Mechanical Characteristics

| | Bulk Cable Weight: | 4 lbs/1000ft |
|--|--------------------|--------------|
|--|--------------------|--------------|

Standards

| UL AWM Style: | 1213 |
|-------------------------|-------------------------|
| Military Specification: | NEMA HP3, MIL-W-16878/4 |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| UL Flammability: | VW-1 |
|--------------------|-----------|
| UL voltage rating: | 600 V RMS |

Plenum/Non-Plenum

Part Number

Variants

| Item # | Color | Footnote |
|---------------|-------------|----------|
| 83005 010100 | Black | E |
| 83005 0101000 | Black | |
| 83005 006100 | Blue, Light | E |
| 83005 0061000 | Blue, Light | ES |
| 83005 001100 | Brown | E |
| 83005 0011000 | Brown | ES |
| 83005 008100 | Gray | E |
| 83005 0081000 | Gray | ES |
| 83005 005100 | Green, Dark | E |
| 83005 0051000 | Green, Dark | ES |
| 83005 003100 | Orange | E |
| 83005 0031000 | Orange | ES |
| 83005 002100 | Red | E |
| 83005 0021000 | Red | ES |
| 83005 007100 | Violet | E |
| 83005 0071000 | Violet | ES |
| 83005 009100 | White | E |
| 83005 0091000 | White | ES |
| 83005 004100 | Yellow | E |
| 83005 0041000 | Yellow | ES |

| Footnote: | E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'. |
|-----------|---|
| Footnote: | S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE) |

© 2019 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.