



Part Number: 83006

Lead Wire, #22 Str SPC, TFE Ins, AWM 1213 105C TYPE E

Request Sample

Product Description

High Temp Plastic Lead Wire, 22AWG (19x34) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
22	19x34	SCC - Silver-coated Copp	per 1
Condu	ictor Count:	1	
Condu	ıctor Size:	2	2 AWG

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	0.048 in	0.009 in

Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.05 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 15.75 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Mil-Std-975M Table 3.16 (single wire)	Mil-Std-975M Table 3.16 (single wire): 4.5 amps

Voltage

Description	Voltage Rating [V]
Mil-W-16878/4	600 V RMS Mil-W-16878/4

Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

	Bulk Cable Weight:	4 lbs/1000ft
--	--------------------	--------------

Standards

UL AWM Style:	1213
Military Specification:	NEMA HP3, MIL-W-16878/4 (Except For Stranding)

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1	
UL voltage rating:	600 V RMS	

Plenum/Non-Plenum

Part Number

Variants

Item #	Color	Footnote
83006 010100	Black	E
83006 0101000	Black	
83006 010500	Black	ES
83006 006100	Blue, Light	E
83006 0061000	Blue, Light	ES
83006 006500	Blue, Light	ES
83006 001100	Brown	E
83006 0011000	Brown	ES
83006 001500	Brown	ES
83006 008100	Gray	E
83006 0081000	Gray	ES
83006 005100	Green, Dark	E
83006 0051000	Green, Dark	ES
83006 005500	Green, Dark	ES
83006 003100	Orange	E
83006 0031000	Orange	ES
83006 002100	Red	E
83006 0021000	Red	
83006 002500	Red	ES
83006 0071000	Violet	ES
83006 007100	Violet	E
83006 009100	White	E
83006 0091000	White	
83006 009500	White	ES
83006 004100	Yellow	E
83006 0041000	Yellow	ES
83006 004500	Yellow	ES

Footnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.
Footnote:	S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE)

© 2019 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief

osure is not to be considered a ations based on their individual	ormation is designed only as a general warranty or quality specification. Regu usage of the product.	atory information is for guidance p	purposes only. Product users are	responsible for determining the ap	plicability of legislation an