

Part Number: 83026	
Lead Wire, #22 Str SPC, TFE Ins	, AWM 1180 300V 200C TYPE EE
😭 Request Sample	
	1

Product Description

High Temp Plastic Lead Wire, 22AWG (19x34) Silver Plated Copper, TFE Insulation, AWM 1180 300V 200C TYPE EE MIL-W-16878/5 1000V 200C

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material No. of Conductors			
AWG	Stranding	Material	No. of Conductors
22	19x34	SCC - Silver-coated Cop	per 1
Condu	uctor Count:		
Condu	uctor Size:	2	22 AWG

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	0.06 in	0.015 in

Outer Jacket Material

Material No Jacket

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR

15.75 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Mil-Std-975M Table 3.16 (single wire)	4.5 amps

Voltage

_			
Description	UL Description	UL Voltage Rating	Voltage Rating [V]
Mil-W-16878/5	UL AWM 1180	300 V RMS	1000 V

Temperature Range

Non-UL Temp Rating:	200°C
UL Temp Rating:	200°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

Bulk Cable Weight:	4 lbs/1000ft
Standards	
UL AWM Style:	1180
Military Specification:	NEMA HP3, MIL-W-16878/5 (Except for Stranding)

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No		

Part Number

Variants

Item # Colo Footnote 83026 010100 Black Е 83026 0101000 Black 83026 010500 ΕS Black 83026 0061000 Blue, Light ES 83026 006100 Blue, Light Е 83026 001100 Brown Е ΕS 83026 0011000 Brown 83026 0081000 Gray ΕS Е 83026 008100 Gray 83026 005100 Green, Dark Е 83026 0051000 Green, Dark ES 83026 003100 Orange Е ΕS 83026 0031000 Orange 83026 002100 Red Е 83026 0021000 Red ES 83026 007100 Violet Е 83026 0071000 Violet ΕS 83026 009100 White Е 83026 0091000 White ΕS Е 83026 004100 Yellow 83026 0041000 Yellow ΕS E - MAY CONTAIN MORE THAN 1 PIECE, MINIMUM LENGTH OF ANY ONE PIECE IS 25'. Footnote S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE) Footnote:

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.