



Product Description

Two 16 AWG stranded (19x29) silver-plated copper conductors, Teflon® (TFE) insulation, silver plated copper braid shield (85% coverage), Teflon® (TFE) jacket.

Technical Specifications

Physical Characteristics (Overall)

Condu	Conductor				
AWG	Stranding	Material		No. of Conductors	
16	19x29	SPCCS - Silver Plated Copper Covered Steel		2	
Conductor Count: 2					
Total Number of Pairs: 1		1			
Conductor Size:		16 AWG			

Insulation

Material	Material Trade Name	Nominal Wall Thickness
TFE - Tetrafluoroethylene	Teflon®	0.011 in

Color Chart

Number	Color
1	White
2	Black

Outer Shield Material

Туре	Material	Coverage [%]
Braid	SPC - Silver Plated Copper	85 %

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	Teflon®	0.197 in	0.011 in

Construction and Dimensions

Lay Length Lay Direction Twists 2 in Left Hand 6 twist/ft Electrical Characteristics Conductor DCR Nominal Outer Shield DCR 4.4 Ohm/1000ft 4.4 Ohm/1000ft						
Electrical Characteristics Conductor DCR Nominal Conductor DCR Nominal Outer Shield DCR 4.4 Ohm/1000ft Capacitance	Cabling	Cabling				
Electrical Characteristics Conductor DCR Nominal Conductor DCR Nominal Outer Shield DCR 4.4 Ohm/1000ft Capacitance	Lay Length Lay Di	rection Twists				
Conductor DCR Nominal Conductor DCR Nominal Outer Shield DCR 4.4 Ohm/1000ft Capacitance	2 in Left Ha	and 6 twist/ft				
Nominal Conductor DCR Nominal Outer Shield DCR 4.4 Ohm/1000ft 4.4 Ohm/1000ft Capacitance Image: Capacitance	Electrical Chara	Electrical Characteristics				
4.4 Ohm/1000ft 4.4 Ohm/1000ft Capacitance	Conductor DCR					
Capacitance	Nominal Conductor DCR Nominal Outer SI		Shield DCR			
	4.4 Ohm/1000ft 4.4 Ohm/1000ft					
Nom. Capacitance Conductor to Conductor Nom. Capacitance Conductor to Other Conductor to Shield	Capacitance					
36 pF/ft 60 pF/ft	36 pF/ft		60 pF/ft			
Shielding: Braid(s)	Shielding: Bra		Braid(s)			

Inductance

Current

Element	Max. Recommended Current [A]
35C Temperature Rise	11 Amps per conductor @ 25°C ambient

Voltage

Non-UL Voltage Rating 600 V RMS

Temperature Range

Operating Temp Range:	-65°C To +200°C

Mechanical Characteristics

Bulk Cable Weight:	33 lbs/1000ft
Max Recommended Pulling Tension:	95.5 lbs
Min Bend Radius/Minor Axis:	2 in

Standards

CPR Euroclass:	Eca
Military Specification:	MIL-W-16878/4 (Type E except stranding), (insulated conductors)
Other Specification:	NEMA HP3

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	600 V RMS
Plenum/Non-Plenum	

Plenum (Y/N):	No

Part Number

Variants

variants		
ltem #	Color	Footnote
83322E 009100	White	E
83322E 0091000	White	E
83322E 009500	White	E
Footnote:		

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.