



Part Number: 83804

Fire Protective Control/Instrumentation, (4) 12 AWG (7x20) TC, FEP/FEP, Foil+TC Braid ShId, CMP

Product Description

Four 12 AWG stranded (7x20) tinned copper conductors, plenum, Teflon® (FEP) insulation, overall Beldfoil® shield (100% coverage) plus tinned copper braid shield (85% coverage), Teflon® (FEP) jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
12	7x20	TC - Tinned Copper	4
Condu	ctor Count:		
Conductor Size:			

Insulation

Material	Material Trade Name	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	Teflon®	0.016 in

Color Chart

Number	Color
1	Black
2	White
3	Red
4	Green

Outer Shield Material

Туре	Layer	Material	Material Trade Name	Coverage [%]
Таре	1	Aluminum Foil-Polyester Tape	Beldfoil®	100 %
Braid	2	TC - Tinned Copper		85 %

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	Teflon®	0.359 in	0.017 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
1.7 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capaci	tance Conductor to Other Conductor to Shield
32 pF/ft	55 pF/ft	
Shielding:		Foil + Braid(s)

Current

Max. Recommended Current [A] 20 Amps per conductor @ 25°C

Voltage

UL Voltage Rating

300 V RMS (UL AWM Style 1424)

Temperature Range

UL Temp Rating:	200°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

Bulk Cable Weight:	138 lbs/1000ft
Max Recommended Pulling Tension:	406 lbs
Min Bend Radius/Minor Axis:	3.75 in

Standards

NEC Articles:	760, 800
NEC/(UL) Specification:	CMP, FPLP
CEC/C(UL) Specification:	CMP

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
	165

Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262	
CSA Flammability:	FT6	
UL voltage rating:	300 V RMS (UL AWM Style 1424)	

Plenum/Non-Plenum

Plenum (Y/N):

Yes

Part Number

Variants		
Item #	Color	Footnote
83804 0021000	Red	С
83804 002500	Red	С
Footnote:		

© 2018 Belden Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.