



Part Number: 8469


Audio/Control/Instrumentation, (9) 18 AWG (19x30) TC, PVC/PVC, CMG

## **Product Description**

Nine 18 AWG stranded (19x30) tinned copper conductors, conductors cabled, PVC insulation, PVC jacket.

# **Technical Specifications**

#### **Physical Characteristics (Overall)**



#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.018 in

## Color Chart

Number	Color
1	Black
2	White
3	Red
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple

# Outer Shield Material



#### **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.364 in	0.037 in

## **Electrical Characteristics**

# Conductor DCR



### Capacitance



#### Current

# Max. Recommended Current [A]

3.5 Amps per conductor @ 25°C

#### Voltage

## UL Voltage Rating

300V RMS (UL AWM Style 2598)

### **Temperature Range**

UL Temp Rating:	60°C (UL AWM Style 2598)
Operating Temp Range:	-20°C To +60°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	89 lbs/1000ft
Max Recommended Pulling Tension:	187 lbs
Min Bend Radius/Minor Axis:	3.75 in

#### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2598 (300 V 60°C)
CPR Euroclass:	Eca

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
LO Directive 2000/33/LC (LLV).	ies
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
UL Voltage Rating:	300 V RMS (UL AWM Style 2598)

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

#### **Part Number**

#### Variants

Item #	Color	Footnote
8469 060100	CHROME	
8469 0601000	CHROME	С
8469 060250	CHROME	С
8469 060500	CHROME	С
8469 0605000	CHROME	

Footnote: C - CRATE REEL PUT-UP.

# © 2018 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.