



P.O. Box 276, Trenton, Ontario, K 8 V 5 R 5  
 Voice: 888 - ELECTRO, Fax: 613 394 - 4101  
 email: info@electrocables.com  
 www.electrocables.com

**Specification Sheet**

Date: 29-Jun-09 Rev. 1

ECI Product#: **5151803TFT4**

Product Description **Shielded 3/c 18/16 Tinned Copper Conductor  
 SR-PVC Insulation  
 O/A Shield & O/A Tinned Copper Drain  
 PVC Jacket FT4 105°C**

Conductor	18 AWG Tinned Copper
Conductor Stranding	16
Nom Cond DC Resistance, ohms/1000 ft	6.7
Insulating Material Type	SR-PVC 105°C
Jacket Material Type	PVC FT4
Finished Cable O.D. , inches	0.209
Total Cable Weight (kgs/km)	44.5
Velocity of Propogation (%)	63%
Nominal Mutual Capacitance, pF/ft	47.0
Conductor Shield Capacitance, pF/ft	85.8
Nominal Impedance (ohms)	60
CSA Certification	CSA CMG 300V, CSA AWM 600V 105°C
UL Certification	UL CM 300V 105°C
EU RoHS	Yes

*(All of the above values are approximated to within 10%)*

**\* Put-ups available in any length required.**