



PRODUCT DATA SHEET

Controlled document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 92094
DESCRIPTION: COMBO RG59 COAXIAL PLUS 18 AWG/2 CONDUCTOR IN ONE JACKET
RATING: UL LISTED AS CL2
UL SUNLIGHT RESISTANT
UL RECOGNIZED COMPONENT AWM STYLE 1354

Construction Parameters:


		OD (in)*
<u>Part 1:</u>	Conductor: 20 AWG (1/.032) Solid Bare Copper	0.032
	Dielectric: Foam Polyethylene color natural	0.144
	Shielding: 95% Copper Braid	0.171
	Jacket: PVC	0.239
<u>Part 2:</u>	Conductor: 18 AWG (16/30) Solid Bare Copper	0.045
	Dielectric: PVC	0.065
<u>Final:</u>	Jacket: One Part 1 and 2 Part 2's are jacket under one jacket.	0.340

Electrical Properties:

	VALUE*
<u>Coax:</u>	
Impedance (ohms):	75
Capacitance (pF/ft):	17
Velocity of Propagation (%):	78
Attenuation** (db/100 ft):	
50 MHz	1.7
216 MHz	3.6
240 MHz	3.8
260 MHz	4.0
270 MHz	4.0
300 MHz	4.3

Cable Cross-section:

(NOT TO SCALE)



Miscellaneous Information:

Coax Jacket Color:	Black
Coax Jacket Print (White):	RG 59/U 20 AWG TYPE CL2 (UL) OR AWM 1354 E100316-I
Final Jacket Color:	White
Final Jacket Print (Black):	CCI 92094 E100316-I 18 AWG/2C & 20 AWG/1C RG 59/U COAX TYPE CL2 (UL) SUN RES
Applicable NEC Article:	725 & 310
Flame rating:	UL-1581 Vertical Tray Flame Test
Sunlight Resistant:	UL-13 Sunlight Resistant Test
Approximate Weight (lb/1000 ft):	65

This product complies with European Directive 2011/65/EU (RoHS-2)
On special orders the customer will accept all factory lengths and ± 10% of total order requested.
A rip cord is added to facilitate jacket removal.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

