



Part Number: 9260

Audio/Control/Instrumentation, (6) 20 AWG (7x28) TC, PVC/PVC, TC Braid Shld, CMG

# **Product Description**

Six 20 AWG stranded (7x28) tinned copper conductors , PVC insulation, tinned copper braid shield (85% shield coverage), PVC jacket.

# **Technical Specifications**

#### **Physical Characteristics (Overall)**

# Conductor AWG Stranding Material No. of Conductors 20 7x28 TC - Tinned Copper 6 Conductor Count: 6 Conductor Size: 20 AWG

#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.017 in

#### **Color Chart**

Number	Color
1	Black
2	White
3	Red
4	Green
5	Orange
6	Blue

## **Outer Shield Material**

Type	Material	Coverage [%]
Braid	TC - Tinned Copper	85 %

## Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.305 in	0.032 in

# **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
9.5 Ohm/1000ft	2.8 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
26 pF/ft	50 pF/ft
Shielding:	Braid(s)

#### Current

Max. Recommended Current [A] 3.2 Amps per conductor @ 25°C

## Voltage



#### **Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 2464)
Operating Temp Range:	-20°C To +80°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	64 lbs/1000ft
Max Recommended Pulling Tension:	90 lbs
Min Bend Radius/Minor Axis:	3.25 in

#### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2464 (300 V 80°C)
CPR Euroclass:	Eca

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No	

## **Part Number**

## Variants

Item #	Color	Footnote
9260 060100	Chrome	
9260 0601000	Chrome	С
9260 060500	Chrome	С
9260 0605000	Chrome	CZ

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

#### © 2018 Belden, Inc

#### All Pights Pasaryad

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.