



Product Description

High Performance Instrumentation, 1 Pair 20AWG (19x32) Tinned Copper, PVC Insulation E2 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC

Technical Specifications

Product Overview

Suitable Applications:	Instrumentation, Sensors, Valves, Positioners, 4-20mA, 0-10V
Construction Details	
Conductor	
Element No. of Elements Siz	ze Stranding Material
Pair(s) 1 20 A	WG 19x32 TC - Tinned Copper
Insulation	
Element Material	Nom. Thickness Nom. Insulation Diameter Color Code
Pair(s) PVC - Polyvinyl Chlorid	le 0.018 in (0.46 mm) 0.072 in (1.8 mm) Black, Red
Outer Shield	
Shield Type Material	Coverage Drainwire Type
Tape Bi-Laminate (Alum+	+Poly) 100% 22 AWG (19x34) TC
Outer Jacket	
Material Nom. 1	Thickness Nom. Diameter
PVC - Polyvinyl Chloride 0.037 in	1 (0.94 mm) 0.221 in (5.61 mm)
Overall Cable Diameter (Nominal)	: 0.221 in (5.61 mm)
Electrical Characteristics	
Electricals	
Element Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond Nom. Capacitance Cond-to-Shield Max. Current
Pair(s) 11.3 Ohm/1000ft	52 pF/ft (170 pF/m) 97 pF/ft (320 pF/m) 3.8 Amps per Conductor at 25°C
Voltage	
UL Voltage Rating	
300 V (PLTC, CMG)	
Mechanical Characteristi	
Temperature	
UL Temperature Operating	
105°C -30°C to +105°	C
Table Notes:	AWM 80°C

Bend Radius

Stationary Min.	Installation Min.
2.2 in (56 mm)	2.2 in (56 mm)

Max. Pull Tension:	54 lbs (24 kg)
Bulk Cable Weight:	29 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance
Flammability / Reaction to Fire:	UL 1685 UL Loading, FT4, T-29-520, IEEE 1202
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 727, Article 800, CMG, ITC, PLTC
AWM Compliance:	AWM 2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision: Revision Number: 0.609 Revision Date: 02-15-2024

Part Numbers

Variants

Item #	Color	UPC	Footnote
9320 0605000	Chrome	612825228936	Z
9320 060U1000	Chrome	612825228912	
9320 060U500	Chrome	612825228929	

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.