

3-CONDUCTOR POWER SUPPLY CORDS (CONT.)

TYPE SV AND SJ RUBBER AND SJO NEOPRENE JACKETED

Mfg. Part No.	AWG (Stranding)	Nom O.D. Ref.	L	Rating	Plug	Cord	Stock No.	Price Each	
								1-24	
● 17425	16 (26 x 30)	0.340"	15'	1625/13	5-15P	SJ	93K2569	23.20	
● 17629	14 (41 x 30)	0.380"	9'	1875/15	5-15P	SJ	96K5645	18.23	
● 17635	14 (41 x 30)	0.380"	15'	1875/15	5-15P	SJ	98K6028	30.29	

(6222)

3-CONDUCTOR POWER SUPPLY CORDS



- NEMA 5-15P Molded PVC Grounding Plug PH-290B, PH-185, or PH-173
- Rated 60°C; 125V, North American Color Coding, UL Listed, CSA Certified

TYPE SVT AND SJT PVC JACKETED

Mfg. Part No.	AWG (Stranding)	Nom. O.D.	L	Rating	Plug	Cord	Stock No.	Price Each	
								1-24	
● 17237	18 (42 x 34)	0.246"	6'	1250/10	290B	SVT	98K6010	4.54	
● 17239	18 (42 x 34)	0.246"	8'	1250/10	290B	SVT	93K2553	5.70	
● 17405	18 (16 x 30)	0.315"	6'	1250/10	290B	SJT	99K5544	3.78	
● 17407	18 (16 x 30)	0.315"	8'	1250/10	290B	SJT	93K2567	6.31	
● 17276	16 (26 x 30)	0.340"	20'	1625/13	185	SJT	93K2563	20.17	

TYPE SV AND SJ RUBBER AND SJO NEOPRENE JACKETED

● 17238	18 (42 x 34)	0.246"	8'	1250/10	290B	SV	36F1038	8.16	
● 17406	18 (16 x 30)	0.315"	6'	1250/10	185	SJ	93K2566	7.11	
● 17408	18 (16 x 30)	0.315"	8'	1250/10	185	SJ	36F857	8.75	
● 17409	18 (16 x 30)	0.315"	8'	1250/10	185	SJO	93K2568	9.00	
● 17412	18 (16 x 30)	0.315"	12'	1250/10	185	SJ	96K5632	13.11	
● 17419	16 (26 x 30)	0.340"	9'	1625/13	185	SJ	96K5633	13.88	
● 17422	16 (26 x 30)	0.340"	12'	1625/13	185	SJ	96K5634	17.37	
● 17425	16 (26 x 30)	0.340"	15'	1625/13	185	SJ	93K2569	23.20	
● 17629	14 (41 x 30)	0.380"	9'	1875/15	173	SJ	96K5645	18.23	
● 17635	14 (41 x 30)	0.380"	15'	1875/15	173	SJ	98K6028	30.29	

(6223)

POWER SUPPLY CORDS WITH CONNECTOR



- Rated 60°C; 125V, Molded Vinyl Grounding Connector, IEC-320-C-13
- International Color Coding, UL Listed, CSA Certified

FOIL SHIELDED, PVC JACKETED

Mfg. Part No.	AWG (Stranding)	Nom. O.D. Ref.	L	Rating	Recep.	Cord	Stock No.	Price Each	
								1-24	
● 17749	18 (42 x 34)	0.270"	6'7"	1250W/10A	C13	SVT	37F3303	5.48	
● 17750	18 (42 x 34)	0.270"	9'10"	1250W/10A	C13	SVT	37F3304	6.27	
● 17619	18 (42 x 34)	0.340"	9'10"	1250W/10A	C13	SJT	93K2638	8.63	
● 17620	16 (65 x 34)	0.365"	6'7"	1625W/13A	C13	SJT	93K2639	7.76	
● 17621	16 (65 x 34)	0.365"	9'10"	1625W/13A	C13	SJT	93K2640	10.84	

UNSHIELDED, PVC JACKETED

● 17518	18 (42 x 34)	0.315"	6'7"	1250W/10A	C13	SJT	96K5641	5.53	
● 17519	18 (42 x 34)	0.315"	9'10"	1250W/10A	C13	SJT	93K2592	7.53	
● 17520	16 (65 x 34)	0.340"	6'7"	1625W/10A	C13	SJT	93K2593	7.39	
● 17521	16 (65 x 34)	0.340"	9'10"	1625W/10A	C13	SJT	93K2594	10.29	
● 17254	18 (42 x 34)	0.246"	7'6"	1250W/10A	C13	SVT	93K2555	5.42	

IEC 320 STD C13 3-CONDUCTOR STRAIGHT PLUG POWER CORDS

Unshielded 3-conductor power supply cord passes a double-molded CEE-22 connector test specifically. Molded PVC plug and connector

Mfg. Part No.	AWG (Stranding)	Nom. O.D.	L	Rating	Recep.	Cord	Stock No.	Price Each	
								1-24	
● 2120H	3 x 1.00	...	8'2"	2500W/10A	C13	HO5VV-F	93K3154	6.57	

(6225)

DETACHABLE POWER SUPPLY CORDS



- 3 Conductor Unshielded PVC Jacketed
- NEMA 6-15P Molded PVC Grounding Plug
- Molded PVC Grounding Connector, IEC 320-C13
- UL Recognized, CSA Certified

Mfg. Part No.	AWG (Stranding)	Nom. O.D.	Length	Rating	Cord	Stock No.	Price Each	
							1-24	
● 17566	18 (42 x 34)	0.246"	6'7"	2500W/10A	SVT	96K5642	6.30	
● 17567	10 C3	0.246"	9'10"	2500W/10A	SVT	93K2602	8.50	
● 17568	18 (42 x 34)	0.315"	6'7"	2500W/10A	SJT	96K5643	6.87	
● 17569	18 (42 x 34)	0.315"	9'10"	2500W/10A	SJT	96K5644	6.76	

(6228)

POWER SUPPLY CORDS WITH RIGHT-ANGLE CONNECTOR



- Rated 60°C; 125V; Dual-Rated at 10A-250V
- International Color Coding, UL Listed, CSA Certified

UNSHIELDED, PVC JACKETED, SJT CORD

Mfg. Part No.	AWG (Stranding)	Nom. O.D.	Length	Rating	Recep.	Stock No.	Price Each	
							1-24	
● 17536	18 (42 x 34)	0.315"	6'7"	1250W/10A	C13	93K2600	5.59	
● 17537	18 (42 x 34)	0.315"	9'10"	1250W/10A	C13	93K2601	5.22	
● 17539	16 (65 x 34)	0.340"	9'10"	1625W/13A	C13	37F3328	7.14	

FOIL SHIELDED, PVC JACKETED, SVT CORD

● 17751	18 (42 x 34)	0.270"	6'7"	1250W/10A	C13	93K2654	4.67	
---------	--------------	--------	------	-----------	-----	---------	------	--

(6226)

RIGHT-ANGLE, FOIL SHIELDED POWER SUPPLY CORDS



- Molded PVC Right-Angle Grounding Connector PH-390 IEC 320-C-13
- NEMA 5-15P Molded Vinyl Grounding Plug, PVC Jacketed

Mfg. Part No.	AWG (Stranding)	L	Rating	Plug	Conn.	Cord	Stock No.	Price Each	
								1-24	
● 17606	18 (41 x 34)	6'7"	1250W/10A	5-15P	C13	SJT	37F3347	7.44	
● 17607	18 (41 x 34)	9'10"	1250W/10A	5-15P	C13	SJT	93K2608	9.53	
● 17608	16 (65 x 34)	6'7"	1625W/13A	5-15P	C13	SJT	93K2609	9.52	
● 17609	16 (65 x 34)	9'10"	1625W/13A	5-15P	C13	SJT	93K2610	12.43	
● 17745	18 (41 x 34)	6'7"	1250W/10A	5-15P	C13	SVT	93K2651	6.83	
● 17746	18 (41 x 34)	9'10"	1250W/10A	5-15P	C13	SVT	93K2652	9.03	

RIGHT ANGLE, UNSHIELDED, PVC JACKETED

● 17506	18 (41 x 34)	6'7"	1250W/10A	5-15P	C13	SJT	96K5638	6.65	
● 17507	18 (41 x 34)	9'10"	1250W/10A	5-15P	C13	SJT	93K2585	8.40	
● 17508	16 (65 x 34)	6'7"	1625W/13A	5-15P	C13	SJT	93K2586	6.27	
● 17509	16 (65 x 34)	9'10"	1625W/13A	5-15P	C13	SJT	93K2587	11.11	

(6143)

3-CONDUCTOR SJ POWER SUPPLY CORD



- NEMA 5-15P molded PVC ground plug
- NEMA 5-15R molded PVC ground connector
- Smooth black PVC jacket
- North American color coding
- UL listed, CSA certified

Special use cord for equipment with built-in receptacle with blades and grounding pin for cord attachment.

Mfg. Part No.	AWG	Nom. O.D. (in.)	Length (ft.)	Rating	Stock No.	Price Each	
						1-24	
● 17461	16 x 3	0.34	10	1625W/13A	45P4168	18.26	

(6145)