

# 952 FLEX-GUARD PE/HD

**SERIES** Heavy Duty Expandable Monofilament Sleeving

## DESCRIPTION

- Braided sleeving produced from .015 mil polyester PET (Polyethylene Terephthalate) monofilament
- Heavy duty protective sleeving
- UL recognized for use up to 125°C
- CSA approved and rated for use up to 125°C
- Standard color: Black or Clear

## FEATURES

- Demonstrates excellent chemical and fungus resistance
- Provides good mechanical properties with additional coverage
- Resistance to abrasion and cut-through make it ideal for many industrial and electrical applications
- Excellent chemical resistance permits use in harsh fluid environments
- Open weave construction allows expansion above or below original diameter
- Easy to apply and slip on quickly over irregular shapes
- Good flexibility retained at low temperatures, allows for easy flexing in any direction
- Can neatly capture a number of different sized items within one length

## APPLICATIONS

- Most commonly used over wires, wire bundles and harnesses, cable assemblies, flat ribbon cable, tubing and hoses to provide a tough, durable protection
- Open weave construction allows for complete drainage, prevents condensation and provides for dissipation of heat and moisture
- Ideal for application in machine tools, automatic equipment and robotics where wires and tubes are required to flex freely during operating cycles
- Suitable for exposure to all weather conditions



DIMENSIONS	PART NUMBERS (COLOR: BLACK)	SIZE NOMINAL ID	SIZE RANGE	APPROX. WEIGHT/1000 FT.	STD. SPOOL PUT-UP
	95220375	3/8"	3/16" - 3/4"	8.3 lbs.	500 ft.
	95220625	5/8"	5/16" - 1"	11.4 lbs.	250 ft.
	95221000	1"	1/2" - 1-1/2"	17.4 lbs.	250 ft.
	95221500	1-1/2"	1" - 2"	28.2 lbs.	250 ft.
	95222000	2"	1-1/2" - 3"	34.8 lbs.	100 ft.
	95223000	3"	2-1/2" - 4-1/2"	43.5 lbs.	100 ft.
	95224000	4"	3" - 5-1/4"	44.0 lbs.	100 ft.

The information provided above represents average values and is believed to be reliable. Alta Technologies, Inc. makes no warranties as to its accuracy and disclaims any liability in connection with its use. It is provided for general use only and should not be incorporated into any specific specifications.

## FLUID RESISTANCE

Testing verifies that there is virtually no effect on the tensile strength and only a slight reduction in elongation (approx. 5%) of FLEX-GUARD PE/HD when exposed to the following fluids: Cleaning Fluid, De-Icing Fluid, Fuel Oil, Gasoline, Hydraulic Fluid, Lubricating Oil, Salt Water and Solvents



## TESTING

### PROPERTIES

Tensile Strength  
Elongation  
Specific Gravity  
Moisture Absorption (24 hours)  
Shrinkage @ 180°C  
Max. Operating Temperature  
Melt Temperature  
Low Temperature Flexibility  
Flexural Modulus 10<sup>3</sup> psi @ 73°F  
Fungus Resistance  
Copper Corrosivity

### TEST METHOD

ASTM D-876  
ASTM D-876  
ASTM D-876  
ASTM D-570  
UL 224  
ASTM D-2117  
MIL I 23053-E  
ASTM D-790  
MIL STD 810 (508)  
MIL I 23053

### PERFORMANCE

90,000 psi  
25%  
1.31  
0.08%  
4%  
125°C  
250°C  
-70°C  
400  
No Growth  
No Effect



**ALTA TECHNOLOGIES, INC.**

P.O. Box 100, Pennington, NJ 08534 | [www.altatechinc.com](http://www.altatechinc.com) | E: [info@altatechinc.com](mailto:info@altatechinc.com) | P: 609-538-9500 | F: 609-538-9501