



PRODUCT DATA SHEET

1530 Shields Drive
 Waukegan, IL 60185
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

PART NUMBER: 988409
DESCRIPTION: RG-213/U COAXIAL CABLE FULL SWEPT PER MIL-C-17
RATING: Mil-C-17 Qualified Products List (QPL)

Construction Parameters:

		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductors:	12.5 AWG (7/.030) Stranded Bare Copper		0.089
Dielectric:	Solid Polyethylene color natural	0.099	0.285
Shielding:	95% Bare Copper Braid		0.315
Jacket:	PVC (Non-Contaminating Vinyl Type IIA))	0.045	0.405

Electrical Properties:

	<u>VALUE*</u>
Conductor Resistance (Max./100 ft)	0.17
Shield Resistance (ohms/1000 ft):	2.9
Impedance (ohms):	50
Capacitance (Max. pF/ft):	32.2
Velocity of Propagation (%):	66
Attenuation (Max. db/100 ft):	
50 MHz	1.2
100 MHz	2.3
400 MHz	4.8
1000 MHz	9.0
SRL (Min. db):	
0.1 Ghz	29
0.5 GHz	26
1.0 GHz	24

Cable Cross-section:

(NOT TO SCALE)



Miscellaneous Information:

Jacket Color: Black
 Jacket Print (white): COLEMAN CABLE 8409F M17/74-RG213 MIL-C-17 OJUD5
 Applicable Mil-C-17: M17/74-RG213
 Approximate Weight (lb/1000 ft): 110

Company Name: _____

Customer Approval: _____

Date: _____

On special orders the customer will accept all factory lengths and ± 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We reserve the right to review and modify all constructions to conform with the latest Regulatory requirement. We disclaim all liability in connection with the use of information contained herein or otherwise. This specification is propriety intellectual property of COLEMAN CABLE. Any information contained herein shall not be disclosed to any party without written consent of COLEMAN CABLE.

Issued: 06/27/05

* = Nominal value
 By: PEP