

Part Number: 9919
Lead Wire, #20 Str TC, PVC Ins, AWM 1007 AWM 1569
😫 Request Sample

Product Description

Low Temp Plastic Lead Wire, 20AWG (7x28) Tinned Copper, PVC Insulation, AWM 1007 AWM 1569 CSA TYPE TR-64 TRSR-64

Technical Specifications

Physical Characteristics (Overall)

Condu	ctor					
AWG	Stranding	Mater	ial	No.	of Conductors	No. of Pairs
20	7x28	TC - Tinned	Copper	1		6
Condu	ctor Count:		1			
Condu	ctor Size:		20 AV	/G		

Insulation

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.069 in	0.016 in	0.015 in

Outer Jacket Material

Material No Jacket

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR

9.4 Ohm/1000ft

Voltage

Temperature Range

Non-UL Temp Rating:	105°C
UL Temp Rating:	105°C

Mechanical Characteristics

Bulk Cable Weight:	5 lbs/1000ft
Min Bend Radius/Installation:	6 in

Standards

UL Rating:	300V RMS, 80°C and 300V, 105°C
OE Rating.	
UL AWM Style:	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)
CSA Rating:	300V RMS, 90°C and 300V, 105°C
CSA AWM Specification:	TRSR-64
CSA Type:	TRSR-64

Applicable Environmental and Other Programs

N/A

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Outdoor:

Flammability, LS0H, Toxicity Testing

No

UL Flammability:	VW-1
CSA Flammability:	
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

/ariants		
ltem #	Color	Footnote
9919 010100	Black	
9919 0101000	Black	Р
9919 013100	Blue, Dark	
9919 0131000	Blue, Dark	Р
9919 001100	Brown	
9919 0011000	Brown	Р
9919 0081000	Gray	Р
9919 005100	Green, Dark	
9919 0051000	Green, Dark	Р
9919 0031000	Orange	Р
9919 002100	Red	
9919 0021000	Red	Р
9919 007100	Violet	
9919 0071000	Violet	Р
9919 009100	White	
9919 0091000	White	Р
9919 004100	Yellow	
9919 0041000	Yellow	Р

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.