



# Part Number: 9987

Lead Wire, #30 Str TC, PVC Ins, AWM 1061 CSA AWM

Request Sample

# **Product Description**

Low Temp Plastic Lead Wire, 30AWG (7x38) Tinned Copper, PVC Insulation, AWM 1061 CSA AWM 300V 80C

# **Technical Specifications**

# **Physical Characteristics (Overall)**

# Conductor AWG Stranding Material No. of Conductors 30 7x38 TC - Tinned Copper 1 Conductor Count: 1

# Insulation

Conductor Size:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.032 in	0.01 in

30 AWG

# Outer Jacket Material



# **Construction and Dimensions**

# Stranding



# **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	
	6.9 Ohm/km	
6.8 Ohm/1000ft		

### High Frequency (Nominal/Typical)

Nom. Insertion Loss
6.9 dB/100m
6.9 dB/100m
6.9 dB/100m

# Voltage

Non-UL Voltage Rating	UL Voltage Rating
300 V	300 V

# **Temperature Range**

Non-UL Temp Rating:	80°C
UL Temp Rating:	80°C

### **Mechanical Characteristics**

Bulk Cable Weight:	0.8 lbs/1000ft

### Dimensions (WxHxD)



### **Standards**

UL Rating:	300V RMS, 80°C
UL AWM Style:	AWM 1061
CSA Rating:	300V RMS, 80°C
CSA AWM Specification:	AWM I A/B
CSA Type:	AWM I, A/B
Military Specification:	N/A

### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	No

### **Part Number**

### Variants

Item #	Color
9987 010100	Black
9987 0101000	Black
9987 0021000	Red
9987 0071000	Violet
9987 009100	White
9987 0091000	White

### © 2019 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.