

"Stay Connected" with



Specialty Power Cords

a PennEngineering® Company

Custom Male T2L Configurations continued

cUL^{us} Listed for Use in the U.S. and Canada Under File E217650

Part No.	Description	Color	Wire		Overall Length A in.	ROJ		Strip Length C in.	Ring Terminal Part No.	Strain Relief	
			Gauge AWG/Cond	Type		B in.	D in.				
L6-15P, 14 Gauge											
S7695	T2L 250V-15A	Black	14-3	SJT	36	2.5	1/2	8145	-	-	-
S7696	T2L 250V-15A	White	14-3	SJT	36	2.5	1/2	8145	-	-	-
S7695G	T2L 250V-15A	Black	14-3	SJT	72	2.5	1/2	8145	-	-	-
L6-30P, 12 Gauge*											
S7705	T2L 250V-30A	Black	12-3	SJT	36	2.5	1/2	8145	-	-	-
S7710	T2L 250V-30A	Black	12-3	STOW	36	2.5	1/2	8145	-	-	-
S7710Q	T2L 250V-30A	Black	12-3	STOW	78	4	1/2	-	4547	5	-
L6-30P, 10 Gauge											
S7700	T2L 250V-30A	Black	10-3	SJT	36	2.5	1/2	6072	-	-	-
S7708	T2L 250V-30A	Black	10-3	STOOW	36	2.5	1/2	6072	-	-	-
L7-15P, 16 Gauge											
S7630	T2L 277V-15A	Black	16-3	SE00W	36	2.5	1/2	8125	-	-	-
S7631	T2L 277V-15A	White	16-3	SE0W	36	2.5	1/2	8125	-	-	-
S7631BQ	T2L 277V-15A	White	16-3	SE0W	36	5	1/2	-	-	-	-
S7631E	T2L 277V-15A	White	16-3	SE0W	36	5.5	1/2	8125	1859	6.5	-
S7631W	T2L 277V-15A	White	16-3	SE0W	36	2.5	5/8	-	-	-	-
S7631D	T2L 277V-15A	White	16-3	SE0W	42	3	1/2	-	-	-	-
S7630FF	T2L 277V-15A	Black	16-3	SE00W	72	2.5	5/8	-	-	-	-
S7630G	T2L 277V-15A	Black	16-3	SE00W	72	2.5	1/2	8125	-	-	-
S7631FF	T2L 277V-15A	White	16-3	SE0W	72	2.5	5/8	-	-	-	-
S7631G	T2L 277V-15A	White	16-3	SE0W	72	2.5	1/2	8125	-	-	-
S7631AU	T2L 277V-15A	White	16-3	SE0W	78	4	1/2	8125	-	-	-
S7631C	T2L 277V-15A	White	16-3	SE0W	78	4	1/2	8125	1859	6	-
S7630H	T2L 277V-15A	Black	16-3	SE00W	84	3	1/2	8125	-	-	-
S7630HH	T2L 277V-15A	Black	16-3	SE00W	84	6	5/8	-	-	-	-
S7631HH	T2L 277V-15A	White	16-3	SE0W	84	6	5/8	-	-	-	-
S7630I	T2L 277V-15A	Black	16-3	SE00W	96	2.5	1/2	8125	-	-	-
S7631BK	T2L 277V-15A	White	16-3	SE0W	96	2.5	5/8	-	-	-	-
S7631AC	T2L 277V-15A	White	16-3	SE0W	108	2.5	5/8	-	-	-	-
S7631J	T2L 277V-15A	White	16-3	SE0W	108	6	5/8	-	-	-	-
S7630AZ	T2L 277V-15A	Black	16-3	SE00W	120	2.5	1/2	-	1859	3.5	-
S7630BA	T2L 277V-15A	Black	16-3	SE00W	120	2.5	1/2	-	-	-	-
S7631AE	T2L 277V-15A	White	16-3	SE0W	120	2.5	5/8	-	-	-	-
L7-15P, 14 Gauge											
S7635	T2L 277V-15A	Black	14-3	SE0W	36	2.5	1/2	8145	-	-	-
S7636	T2L 277V-15A	White	14-3	SE0W	36	2.5	1/2	8145	-	-	-
L7-15P, 12 Gauge											
S7637	T2L 277V-15A	Black	12-3	SJTW	36	2.5	1/2	8145	-	-	-
S7638	T2L 277V-15A	White	12-3	SJTW	36	2.5	1/2	8145	-	-	-

*For 12 AWG applications, the power cords are derated to 20 Amp.

- DFARS Compliant