

Y-CY-JB flexible, Cu-screened, transparent, EMC-preferred type, meter marking

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
16153	4 G 16	25,3	807,0	1380,0	6
16154	5 G 16	28,0	940,0	1553,0	6
16469	4 G 25	31,1	1169,0	1890,0	4
16155	5 G 25	34,3	1420,0	2270,0	4
16470	4 G 35	33,9	1680,0	2390,0	2
16156	5 G 35	37,8	2020,0	2885,0	2

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
16471	4 G 50	40,1	2370,0	3315,0	1
16119	5 G 50	45,0	2880,0	4150,0	1
16472	4 G 70	46,0	3257,0	4600,0	2/0
16473	4 G 95	51,2	4060,0	6060,0	3/0
16474	4 G 120	56,3	5231,0	7315,0	4/0
16247	4 G 150	64,7	7760,0	9340,0	300 kcmil
16319	4 G 185	69,5	8104,0	11120,0	350 kcmil

A

Dimensions and specifications may be changed without prior notice. (RA01)



Suitable accessories can be found in Chapter X.

- Cable Gland - HELUTOP® HT-MS-EP4