



For more Information
please call

1-800-Belden1



General Description:

Light Duty SMPTE 311M Cable, 4 power conductors, SM fibers w/24 and 20 AWG stranded (7x32 and 19x32) TC conductors, PO insulation, TC braid shield (85% coverage), Belflex® jacket.

Usage (Overall)

Suitable Applications: SMPTE 311M Camera Cable

Multi Conductor

Physical Characteristics

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (mm)
2	24	7x32	TC - Tinned Copper	0.610
4	20	19x32	TC - Tinned Copper	0.940

Insulation

Insulation Material:

Insulation Material	Dia. (mm)	AWG
PO - Polyolefin	1.575	20
PO - Polyolefin	1.219	24

Insulation Color Code Chart:

Number	Color	Description
1	Red	24 AWG
2	Gray	24 AWG
3	White	20 AWG
4	White	20 AWG
5	Black	20 AWG
6	Black	20 AWG

Individual Shield

Electrical Characteristics

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/km)
24 AWG	76.447
20 AWG	28.873

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
11.484

Fiber

Physical Characteristics

Fiber Type: Non-Dispersion Shifted, Single Mode/125/900 Micron

Number of Fibers: 2

Mode Field Diameter @ 1310nm: 9.5 +/-1 microns

Clad Diameter: 125 microns

Core-clad Concentricity Error: < to 1 micron

Primary Coating Material: Acrylate

Buffer Tube Diameter: 900 microns

Buffer Tube Material: PVC - Polyvinyl Chloride

Buffer Tube Color Code Chart:

Number	Color
1	Blue
2	Yellow

Optical Characteristics

Maximum Attenuation @ 1310nm: 0.8 dB/km

Physical Characteristics (Overall)

Conductor

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	TC - Tinned Copper	85.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Belflex®	PVC Blend - Polyvinyl Chloride Blend

Strength Member

Overall Strength Member Diameter: .085

Strength Member Material: 302 Stainless Steel

Overall Cable

Overall Nominal Diameter: 9.068 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

Bulk Cable Weight: 119.056 Kg/Km

Max. Recommended Pulling Tension: 2001.690 N

Min. Bend Radius/Minor Axis: 63.500 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC(UL) Rating: UL AWM Style 20907 (300V 60°C)

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

Other Specification: SMPTE 311

Flame Test

UL Flame Test: VW-1

Suitability

Suitability - Indoor: Yes

Suitability - Outdoor: Yes

Sunlight Resistance: Yes

Suggested Connectors: SMPTE 304M Connectors

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 7804P

Non-Plenum Number: 7804C, 7804R, 7804WB

Electrical Characteristics (Overall)

Other Electrical Characteristic 1: Auxillary Conductors: DC Loop Resistance - 30 Ohms/km nom. (9.1 Ohms/1000ft.) Min. Insulation Resistance - 10, 000 Megaohms x km Dielectric Strength - 1750 V RMS. Signal Conductors: DC Loop Resistance - 150 Ohms/km nom. (45.7 Ohms/1000 ft.) Insulation Resistance - 10, 000 Megaohms/1000 ft. Dielectric Strength: 1750 V RMS

Notes (Overall)

Notes: Bend Radius is based upon (FOTP-37) @ 20°C. Plenum version and other conductor counts/diameters available by special order.

Put Ups and Colors:

METRIC MEASUREMENT VERSION

7804LW Composite - SMPTE 311M HDTV Cable

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7804LW 0101000	1,000 FT	73.000 LB	BLACK		COMPOSITE CABLE BRD PVC
7804LW 010500	500 FT	37.000 LB	BLACK		COMPOSITE CABLE BRD PVC

Revision Number: 0 Revision Date: 03-27-2015

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.