



| ADVANCED CABLE TIES PART NUMBER | BUNDLE DIAMETER | | A | B | C | D | E | F | MIN LOOP TENSILE LBS (n) | ANSI/UL 94 MH FLAMABILITY RATING | PLENUM RATING |
|------------------------------------|------------------|-----------------------|----------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--------------------------------|--|---------------|
| | MIN IN (mm) | MAX IN (mm) | IN (mm) +/- .125 (3.175mm) | IN (mm) +/- .005 (.127mm) | IN (mm) +/- .005 (.127mm) | IN (mm) +/- .020 (.508mm) | IN (mm) +/- .020 (.508mm) | IN (mm) +/- .030 (.762mm) | | | |
| AP(R, L)-04-18-30 | .062 (1.57mm) | .874 (22.2mm) | 4.125 (104.775mm) | .042 (1.066mm) | .095 (2.413mm) | .180 (4.572mm) | .150 (3.810mm) | .220 (5.588mm) | 18 (80) | V-2 | N/A |
| AP(R, L)-06-18-30 | .062 (1.57mm) | 1.500 (38.1mm) | 6.187 (157.149mm) | .042 (1.066mm) | .095 (2.413mm) | .180 (4.572mm) | .150 (3.810mm) | .220 (5.588mm) | 18 (80) | V-2 | N/A |
| AP(R, L)-08-18-30 | .062 (1.57mm) | 2.187 (55.5mm) | 8.187 (207.949mm) | .042 (1.066mm) | .095 (2.413mm) | .180 (4.572mm) | .150 (3.810mm) | .220 (5.588mm) | 18 (80) | V-2 | N/A |
| AP(R, L)-05-40-30 | .062 (1.57mm) | 1.437 (36.423mm) | 5.840 (148.336mm) | .049 (1.244mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | N/A |
| AP(R, L)-08-40-30 | .062 (1.57mm) | 2.375 (60.325mm) | 8.875 (225.425mm) | .049 (1.244mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | N/A |
| AP(R, L)-11-40-30 | .062 (1.57mm) | 3.375 (85.725mm) | 10.968 (278.587mm) | .054 (1.371mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | N/A |
| AP(R, L)-14-40-30 | .062 (1.57mm) | 4.000 (101.6mm) | 14.250 (361.950mm) | .054 (1.371mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | N/A |
| AP(R, L)-07-50-30 | .062 (1.57mm) | 1.875 (47.625mm) | 7.562 (192.075mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | N/A |
| AP(R, L)-11-50-30 | .062 (1.57mm) | 3.062 (77.775mm) | 11.250 (285.751mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | N/A |
| AP(R, L)-14-50-30 | .062 (1.57mm) | 4.000 (101.600mm) | 14.250 (361.951mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | N/A |
| AP(R, L)-08-120-30 | .187 (4.75mm) | 2.06 (52.3mm) | 8.700 (220.980mm) | .076 (1.930mm) | .300 (7.620mm) | .490 (12.446mm) | .300 (7.620mm) | .500 (12.700mm) | 120 (534) | V-2 | N/A |
| AP(R, L)-14-120-30 | .187 (4.75mm) | 4.0625 (103.187mm) | 15.093 (383.362mm) | .076 (1.930mm) | .300 (7.620mm) | .490 (12.446mm) | .300 (7.620mm) | .500 (12.700mm) | 120 (534) | V-2 | N/A |



ADVANCED CABLE TIES – HEAT STABILIZED CABLE TIES

COLOR DESIGNATIONS:
30 = BLACK HEAT STABILIZED

MATERIAL:
NYLON 6/6 POLYAMIDE

SHEET 1 OF 1

REV.: A

DRAWING NO.: 30-A

| | | | | | | | | | |
|-----|----------|----|-----|---------|-----------------|----------|----------|-------|-------|
| A | 12/22/14 | JA | KT | KT | INITIAL RELEASE | DRAWN BY | DATE | CHECK | SCALE |
| REV | DATE | BY | CHK | APPROVE | DESCRIPTION | JA | 12/22/14 | KT | NONE |

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.