



| ADVANCED CABLE TIES PART NUMBER | BUNDLE DIAMETER | | A | B | C | D | E | F | MIN LOOP TENSILE LBS (n) | ANSI/UL 94 MH FLAMABILITY RATING | PLENUM RATING |
|------------------------------------|-------------------|----------------------|----------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--------------------------------|--|---------------|
| | MIN IN (mm) | MAX IN (mm) | IN (mm) +/- .125 (3.175mm) | IN (mm) +/- .005 (.127mm) | IN (mm) +/- .005 (.127mm) | IN (mm) +/- .020 (5.08mm) | IN (mm) +/- .020 (5.08mm) | IN (mm) +/- .030 (.762mm) | | | |
| AP(R, L)-07-50-9 | .062 (1.57mm) | 1.875 (47.625mm) | 7.562 (192.075mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | AH-2 |
| AP(R, L)-07-50-0 | .062 (1.57mm) | 1.875 (47.625mm) | 7.562 (192.075mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | AH-2 |
| AP(R, L)-11-50-9 | .062 (1.57mm) | 3.062 (77.775mm) | 11.250 (285.751mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | AH-2 |
| AP(R, L)-11-50-0 | .062 (1.57mm) | 3.062 (77.775mm) | 11.250 (285.751mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | AH-2 |
| AP(R, L)-14-50-9 | .062 (1.57mm) | 4.000 (101.600mm) | 14.250 (361.951mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | AH-2 |
| AP(R, L)-14-50-0 | .062 (1.57mm) | 4.000 (101.600mm) | 14.250 (361.951mm) | .052 (1.320mm) | .180 (4.572mm) | .300 (7.620mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | AH-2 |
| AP(R, L)-17-50-9 | .270 (7.000mm) | 4.520 (115mm) | 17.09 (434.160mm) | .060 (1.524mm) | .188 (4.775mm) | .317 (8.051mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | N/A |
| AP(R, L)-17-50-0 | .270 (7.000mm) | 4.520 (115mm) | 17.09 (434.160mm) | .060 (1.524mm) | .188 (4.775mm) | .317 (8.051mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | N/A |
| AP(R, L)-21-50-9 | .350 (9.000mm) | 5.860 (149.000mm) | 21.680 (550.670mm) | .060 (1.524mm) | .188 (4.775mm) | .317 (8.051mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | N/A |
| AP(R, L)-21-50-0 | .350 (9.000mm) | 5.860 (149.000mm) | 21.680 (550.670mm) | .060 (1.524mm) | .188 (4.775mm) | .317 (8.051mm) | .215 (5.461mm) | .305 (7.747mm) | 50 (222) | V-2 | N/A |



ADVANCED CABLE TIES – 50 LB. (222n) STANDARD SERIES
CABLE TIES

COLOR DESIGNATIONS:
0 = UV BLACK 9 = NATURAL

MATERIAL:
NYLON 6/6 POLYAMIDE

SHEET 1 OF 1

REV.: A

DRAWING NO.: 50-A

| | | | | | | | | | |
|-----|----------|----|-----|---------|-----------------|----------|------------|-------|-------|
| A | 12/22/14 | JA | KT | KT | INITIAL RELEASE | DRAWN BY | DATE | CHECK | SCALE |
| REV | DATE | BY | CHK | APPROVE | DESCRIPTION | JA | 12/22/2014 | KT | NONE |

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.