



| ADVANCED CABLE TIES PART NUMBER | A OUTSIDE DIAMETER | B (Nominal ID) | C WALL THICKNESS | D RIGHT HAND PITCH | MAX. OPERATING TEMPERATUR E | MIN. OPERATING TEMPERATUR E | ABRASION RESISTANCE (TABER) | WATER ABSORPTION % (D-570) | DI-ELECTRIC CONSTANT (D-150) | UL COMPLIANCE | REGULATORY COMPLIANCE |
|------------------------------------|---|---------------------|---------------------------------------|--|--------------------------------------|--------------------------------------|-----------------------------------|----------------------------------|------------------------------------|---------------|--------------------------|
| AL-CWP-125 | .125 +/- .020 (3.175mm +/- .508mm) | .061 (1.594mm) | .032 +/- .010 (.812mm +/- .254mm) | .187 +/- .062 (4.749mm +/- 1.587mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |
| AL-CWP-187 | .187 +/- .020 (4.762mm +/- .508mm) | .127 (3.225mm) | .030 +/- .010 (.762mm +/- .254mm) | .250 +/- .062 (6.350mm +/- 1.587mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |
| AL-CWP-250 | .250 +/- .020 (6.35mm +/- .508mm) | .160 (4.064mm) | .045 +/- .010 (1.143mm +/- .254mm) | .375 +/- .125 (9.525mm +/- 3.175mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |
| AL-CWP-375 | .375 +/- .020 (9.525mm +/- .508mm) | .271 (6.833mm) | .052 +/- .010 (1.320mm +/- .254mm) | .438 +/- .125 (11.125mm +/- 3.175mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |
| AL-CWP-500 | .500 +/- .025 (12.700mm +/- .635mm) | .376 (9.550mm) | .062 +/- .010 (1.574mm +/- .254mm) | .563 +/- .125 (14.300 +/- 3.175mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |
| AL-CWP-625 | .625 +/- .025 (15.875mm +/- .635mm) | .501 (12.725mm) | .062 +/- .010 (1.574mm +/- .254mm) | .625 +/- .250 (15.875mm +/- 6.350mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |
| AL-CWP-750 | .750 +/- .025 (19.050mm +/- .635mm) | .620 (15.748mm) | .065 +/- .010 (1.651mm +/- .254mm) | .750 +/- .250 (19.050mm +/- 6.350mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |
| AL-CWP-1000 | 1.000 +/- .035 (25.400mm +/- .889mm) | .840 (21.336mm) | .080 +/- .015 (2.032mm +/- .381mm) | 1.000 +/- .250 (25.400 +/- 6.350mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |
| AL-CWP-1250 | 1.250 +/- .035 (31.750mm +/- .889mm) | 1.070 (27.178mm) | .090 +/- .015 (2.286mm +/- .381mm) | 1.250 +/- .250 (31.750mm +/- 6.350mm) | 190°F/88°C | -76°F/-60°C | 20 mg LOSS PER M CYCLES | .03 | 2.6 | UL RECOGNIZED | RoHS |



ADVANCED CABLE TIES – SPIRAL WRAP

COLOR DESIGNATIONS:

0 = UV BLACK 9 = NATURAL

MATERIAL:

Low Density Polyethylene

SHEET 1 OF 1

REV.: A

DRAWING NO.: SPIRAL WRAP-A

DRAWN BY

DATE

CHECK

SCALE

REV

DATE

BY

CHK

APPROVE

DESCRIPTION

JA

4/14/14

KT

NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.