


ADVANCED CABLE TIES PART NUMBER			BUNDLE DIAMETER		A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	F IN (mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING
			MIN IN (mm)	MAX IN (mm)								
AP(R, L)-04-18-ID-9			.230 (6.000mm)	.820 (21.000mm)	4.055 (103.000mm) +/- .039 (1.000mm)	2.874 (73.000mm) +/- .039 (1.000mm)	.094 (2.400mm) +/- .010 (.250mm)	.307 (7.800mm) +/- .014 (.360mm)	.968 (24.600mm) +/- .020 (.520mm)	.045 (1.140mm) +/- .010 (.250mm)	18 (80)	V-2
												
			ADVANCED CABLE TIES – 18 LB. (80n) IDENTIFICATION SERIES CABLE TIES									
								COLOR DESIGNATIONS: 9 = NATURAL		MATERIAL: NYLON 6/6 POLYAMIDE		
								SHEET 1 OF 1	REV.: A	DRAWING NO.: 4-ID-A		
A	4/29/14	JA	KT	KT	INITIAL RELEASE			DRAWN BY	DATE	CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			JA	4/29/14	KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.