


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	F IN (mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MII FLAMABILITY RATING
	MIN IN (mm)	MAX IN (mm)								
AP(R, L)-07-50-ID-9	.47 (12.0mm)	1.81 (46.0mm)	7.913 (201.000mm) +/- .098 (2.500mm)	6.614 (168.000mm) +/- .059 (1.500mm)	.180 (4.580mm) +/- .012 (.300mm)	.512 (13.000mm) +/- .017 (.430mm)	1.098 (27.900mm)	.056 (1.140mm) +/- .010 (.250mm)	50 (222)	V-2
AP(R, L)-07-50-ID-0	.47 (12.0mm)	1.81 (46.0mm)	7.913 (201.000mm) +/- .098 (2.500mm)	6.614 (168.000mm) +/- .059 (1.500mm)	.180 (4.580mm) +/- .012 (.300mm)	.512 (13.000mm) +/- .017 (.430mm)	1.098 (27.900mm)	.056 (1.140mm) +/- .010 (.250mm)	50 (222)	V-2
AP(R, L)-14-50-ID-9	.47 (12.0mm)	3.77 (96.0mm)	13.625 (346.075mm) +/- .098 (2.500mm)	13.250 (336.550mm) +/- .059 (1.500mm)	.187 (4.750mm) +/- .012 (.300mm)	.511 (12.979mm) +/- .017 (.430mm)	10.670 (27.102mm)	.055 (1.397mm) +/- .010 (.250mm)	50 (222)	V-2
AP(R, L)-14-50-ID-0	.47 (12.0mm)	3.77 (96.0mm)	13.625 (346.075mm) +/- .098 (2.500mm)	13.250 (336.550mm) +/- .059 (1.500mm)	.187 (4.750mm) +/- .012 (.300mm)	.511 (12.979mm) +/- .017 (.430mm)	10.670 (27.102mm)	.055 (1.397mm) +/- .010 (.250mm)	50 (222)	V-2
										
						ADVANCED CABLE TIES – 50 LB (222n) IDENTIFICATION SERIES CABLE TIES				
						COLOR DESIGNATIONS: 0 = BLACK 9 = NATURAL		MATERIAL: NYLON 6/6 POLYAMIDE		
						SHEET 1 OF 1		REV.: A		DRAWING NO.: ID-A
A	12/23/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	12/23/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.