



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER	COATING	A - LENGTH IN (mm)	B - WIDTH IN (mm)	C - THICKNESS IN (mm)	D - HEAD SIZE IN (mm)	MAX OPERATING TEMPERATURE F (C)	MIN OPERATING TEMPERATURE F (C)	MIN LOOP TENSILE LBS (n)	REGULATORY APPROVALS
	MAX IN (mm)									
AL-08-100-SS-LD-CT-C	2.360 (60.000mm)	POLYESTER	7.870 (200.000mm)	.270 (7.000mm)	.011 (.300mm)	.344 (8.740mm)	302 (150)	-112 (-80)	100 (444)	UL 90ZA
AL-14-100-SS-LD-CT-C	4.130 (105.000mm)	POLYESTER	14.170 (360.000mm)	.270 (7.000mm)	.011 (.300mm)	.344 (8.740mm)	302 (150)	-112 (-80)	100 (444)	UL 90ZA
AL-24-100-SS-LD-CT-C	5.900 (150.000mm)	POLYESTER	24.010 (610.000mm)	.270 (7.000mm)	.011 (.300mm)	.344 (8.740mm)	302 (150)	-112 (-80)	100 (444)	UL 90ZA
AL-30-100-SS-LD-CT-C	7.870 (200.000mm)	POLYESTER	29.520 (750.000mm)	.270 (7.000mm)	.011 (.300mm)	.344 (8.740mm)	302 (150)	-112 (-80)	100 (444)	UL 90ZA
AL-08-250-SS-LD-CT-C	2.360 (60.000mm)	POLYESTER	7.870 (200.000mm)	.470 (12.000mm)	.013 (.350mm)	.563 (14.280mm)	302 (150)	-112 (-80)	250 (1,112)	UL 90ZA
AL-14-250-SS-LD-CT-C	4.130 (105.000mm)	POLYESTER	14.170 (360.000mm)	.470 (12.000mm)	.013 (.350mm)	.563 (14.280mm)	302 (150)	-112 (-80)	250 (1,112)	UL 90ZA
AL-24-250-SS-LD-CT-C	5.900 (150.000mm)	POLYESTER	24.010 (610.000mm)	.470 (12.000mm)	.013 (.350mm)	.563 (14.280mm)	302 (150)	-112 (-80)	250 (1,112)	UL 90ZA
AL-30-250-SS-LD-CT-C	7.870 (200.000mm)	POLYESTER	29.520 (750.000mm)	.470 (12.000mm)	.013 (.350mm)	.563 (14.280mm)	302 (150)	-112 (-80)	250 (1,112)	UL 90ZA



**ADVANCED CABLE TIES – COATED LADDER STAINLESS STEEL
CABLE TIES**

MATERIAL DESIGNATION: SS = STAINLESS STEEL
MATERIAL: **316 STAINLESS STEEL**

SHEET 1 OF 1 **REV.: A** **DRAWING NO.: SS-LD-CT-A**

A	4/16/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	4/16/2014	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.