

DATE	LET	REVISION	BY	CHK	APPROVALS
11-19-81	A	REVISED & REDRAWN ROPED TABLE	JAC	WJ	
	B	ECD16380-100(1)DD FOR-00,-01 WAS .158-.155(2)ADD DES ACT STICKER	PB	PB	SKP

CURRENT DESIGN ACTIVITY CAGE CODE 97424

AMETEK

AEROSPACE WILMINGTON, MA.

NOTES:

- CONDUCTORS TO BE STRANDED SILVER COATED COPPER WIRE WITH WRAPPED TEFLON INSULATION, IN ACCORDANCE WITH M16878/21 AND TABLE.
- CONDUCTORS TO BE TWISTED AND SHIELDED WITH #36 AWG SILVER PLATED COPPER, WRAPPED TEFLON JACKET, IN ACCORDANCE WITH MIL-C-55021 AND TABLE.

MAY BE PURCHASED FROM:

ALPHA WIRE CORPORATION
NEW YORK 14, NEW YORK

AMERICAN SUPER-TEMPERATURE WIRES, INC.
WINOOSKI, VERMONT

WIRECRAFT PRODUCTS, INC.
WEST BROOKFIELD, MASS.

325013-01	20	19/32	.040	.158-.145	RED-GREEN	WHITE
325013-00	20	19/32	.040	.158-.145	BLACK-WHITE	WHITE
PART NUMBER	AWG SIZE	STRANDING	CONDUCTOR DIA. NOMINAL	CABLE OUTSIDE DIA.	CONDUCTOR COLORS	JACKET COLOR

DRAWN	CHECKED	ENG. APPR.	ENG. APPR.	ENG. APPR.	APPROVED	REAPPROVE
MICHAUD	R. DUVAL				RVS	SKP
12-29-59	12-29-59				12-25-59	1/17/01
UNLESS OTHERWISE SPECIFIED						
BREAK SHARP EDGES .005-IN APPROX.	<input checked="" type="checkbox"/>	SURFACE POLISHING PER AMS: 844.1		ALL DIMENSIONS APPLICABLE AFTER SURFACE TREATMENT		
ALLOWABLE TOLERANCES						
FRACTIONS	DECIMALS	ANGLES	STOCK THICKNESS COMMERCIAL	DRILLED HOLES AND VEE	NEXT ASS'Y. USED ON	
2 PL. 9 JS	2 PL. 1.02	2 P			APPLICATION	
STOCK SIZE			HEAT TREAT		THREADS PER HANDBOOK H-28 AND MIL-STD-8	DIMENSIONING & TOLERANCING PER ANSI Y14.5
MATERIAL SPEC.		FINISH SPEC.				
				WEIGHT		CODE IDENT. No. 50625
				DO NOT SCALE DWG.		CONTRACT No.
						SIZE B
						DRAWING NUMBER 325013
						SHEET 1 OF 1

Revere CORPORATION OF AMERICA
WALLINGFORD, CONNECTICUT

WIRECRAFT
/TRUETE

CABLE - TEFLON JACKETED
SHIELDED
2 CONDUCTOR

ALPHEMIE 30-518

AMETEK-Proprietary; 01-7-30704; ISSUED FOR PRODUCTION
#EC's Released/Required: -NONE-