


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A	B	C	D	E	F	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MII FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)	IN (mm) +/- .125 (3.175mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .030 (.762mm)			
AP(R, L)-04-18-9	.062 (1.57mm)	.874 (22.2mm)	4.125 (104.775mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-04-18-0	.062 (1.57mm)	.874 (22.2mm)	4.125 (104.775mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-06-18-9	.062 (1.57mm)	1.500 (38.1mm)	6.187 (157.149mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-06-18-0	.062 (1.57mm)	1.500 (38.1mm)	6.187 (157.149mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-08-18-9	.062 (1.57mm)	2.187 (55.5mm)	8.187 (207.949mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-08-18-0	.062 (1.57mm)	2.187 (55.5mm)	8.187 (207.949mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
											
ADVANCED CABLE TIES – 18 LB. (80n) MINIATURE SERIES CABLE TIES											
									<b>COLOR DESIGNATIONS:</b> 0 = UV BLACK    9 = NATURAL		<b>MATERIAL:</b> <b>NYLON 6/6 POLYAMIDE</b>
						SHEET 1 OF 1		REV.: A		DRAWING NO.: 18-A	
A	12/22/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY		DATE		CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA		12/22/14		KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.