



NOTES:

1. MATERIALS

1.1 CABLE: [7/0.12BCX1P+7/0.20BCX2C+AM+7/0.12BC+B(16/3/0.12ALM)]+BLACK PVC JACKET.
 OD=∅4.5±0.15MM.

CABLE MARKING:USB 2.0 CABLE FULLY RATED 30V 80°C

1.2 USB 2.0 A TYPE MALE: SOLDER TYPE,
 GOLD PLATED CONTACTS, NICKEL PLATED SHELL.

1.3 P2: USB A TYPE FEMALE: SOLDER TYPE,
 GOLD FLASH CONTACTS, NICKEL PLATED SHELL.

1.4 ALL HOOD: MOLDED BLACK PVC.

2.1 100% OPEN AND SHORT TEST.

3. PACKAGING:1PCS/PE BAG.

4. ALL MATERIAL BE ROHS COMPLIANT.

PIN OUT

P1	P2	
1	1	RED
2	2	WHITE
3	3	GREEN
4	4	BLACK
SHELL		SHELL (BRAID+DRAIN)

P/N

TYPE	L
U2-AAMF-10	3050±70MM
U2-AAMF-15	4575±70MM

LENGTH TOLERANCE: X. ± 0.5 .X ± 0.2 .XX ± 0.1	SCALE: FREE	CUS. NAME:			ENG: MerLin
ANGLE TOLERANCE: X° ±3° .X° ±1°	UNIT: mm		PRODUCT NO:	CUSTOMER NO: P/N	CHECKED:
VERSION: 00	PAGE: 1/1		DRAWING NO: 0687	PRODUCT DESCRIPTION: USB 2.0 AM /AF	APPROVED:

00	NEW ISSUE	2013-04-18
REV.	MODIFY DESCRIPTION	DATE