


E5F1001 Cord Sets - DataTuff® Cat 5e IP20 RJ45 Cord Set

Preview Document. Not Live Data.



For more Information
please call

1-800-Belden1

Description

1 ft. (0.3 M), Unshielded with solid conductors (ref: Belden Bonded-Pair Cable 7923A). Cable Rating NEC: CMR, CMX-Outdoor. CEC: CMR FT4. MSHA.

Notes (Overall):

Notes For additional information about this product, visit our web site at <http://www.belden.com>

Cable:

Description	4 pair, 24 AWG bare copper, Polyolefin Insulation, Bonded pairs, Industrial Grade PVC Oil Res, Sun Res, P-MSHA, CMR, CMX-Outdoor, FT4.
Part Number	7923A
Shielding	Unshielded
Electrical Performance	Category 5e
Maximum Operating Voltage	300 V RMS
Applicable Standards	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, EtherNet/IP(tm) Specification, UL 1666 Riser

Connectors:

Description	RJ45 plugs Suitable for use in IP20 unsealed applications
Connector Type	Cat 5e
Sealing	Suitable for IP20
Connector Interface	IEC 60603-7
Shielding	Unshielded
Electrical Performance	Cat 5e
Maximum Operating Voltage	300 V RMS
Applicable Standards	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, EtherNet/IP Specification

Assembly:

Part Number	E5F1001
Electrical Performance	Category 5e
Maximum Operating Voltage	300 V RMS
Storage Temperature Range	-40°C To +70°C
Installation Temperature Range	-10°C To +60°C
Operating Temperature Range	-10°C To +60°C
Applicable Standards	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801
Shielding	Unshielded
Length	1 ft. (0.3 M)
Notes	US Patent #'s 5, 606, 151; 5, 734, 126, EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc.

E5F1001 Cord Sets - DataTuff® Cat 5e IP20 RJ45 Cord Set

© 2013 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.