


**ENGINEERING NOTES:**

1. Optical Insertion Loss IL < 55dBm (In compliance to Method IEC 60793-1-1)
2. Back Reflection Br < 55dB. (Optical Endface to comply to GR-326 section 44.5)
3. Optical end face must comply to IPC-8497-1
4. Assembly must comply to GEPCO assembly instruction SQL-04-EB04.
5. Cable must be free of debris and any damage to jacket.

<p>DESCRIPTION</p> <p>TACBeam 4ch EB Singlemode OS2 fiber Breakout type "BX" To SC-DUP SM UPC</p>	 <p>1770 Birchwood Avenue Des Plaines, IL 60018 847-795-9555 / 800-966-0069</p>
<p>APPROVAL:</p>	<p>DATE:</p>
<p>REVISION: 1</p>	<p>DATE: 4/11/13</p>
<p>WITNESS:</p>	<p>DATE:</p>
<p>CUSTOMER: IEWC</p>	<p>Fax: 847-795-8770 www.Gepco.com</p>
<p>PART #</p>	<p>GTSEBPM04-23-SC</p>
<p>DRAWING</p>	<p>GTSEBPM04-23-SC</p>
<p>PAGE: 1 OF 1</p>	<p>SCALE: 1:1</p>
<p>SO:</p>	<p>DRAWN BY: PDS</p>

The information set forth in this document is the proprietary, confidential, sole and exclusive intellectual property of General Cable Industries, Inc. and its' related entities, which may not be reproduced, transmitted, copied or shared with any third party without the prior written approval of General Cable Industries, Inc. The images depicted herein are copyright protected by General Cable Industries, Inc.

