



ATLAS WIRE, LLC
1601 GLENLAKE AVENUE
ITASCA, IL 60143
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001 and TS16949
Itasca, IL 60143
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

**#14 19/0147 BC 1/64 PVC .005 NYLON
RoHS COMPLIANT**

**MTW OR THHN/THWN-2 600v GASOLINE AND OIL RESISTANT II OR
AWM STYLE 1452 90c 1000v OR AWM STYLE 1316 105c 600v
AWM STYLE 1408 90c 600v TYPE T90 NYLON OR TWN75
CSA AWM 1 A/B 90c 300v FT-1**

CONDUCTOR: #14 19/0147 BARE COPPER
NOMINAL O.D. .071"
APPROXIMATE CIRCULAR MILL AREA 4,106
WEIGHT PER THOUSAND FEET 12.80#
BASIC SPECIFICATION ASTM B-8
ASTM B-286

PVC: TEMPERATURE RATING 105c
ELONGATION 330% AVERAGE
SPECIFIC GRAVITY 1.32
DUROMETER (SHORE) 46 (D)
MINIMUM TENSILE STRENGTH 3500 PSI
OXYGEN INDEX 30.5
BRITTLE POINT -18c
SPARK TESTED 10,000 VOLTS

NYLON: ELONGATION 300%
TENSILE STRENGTH 11,500 PSI
SPECIFIC GRAVITY 1.13
OVERALL DIAMETER .113"
WEIGHT PER M FEET 16.22#

USE: INTERNAL WIRING OF APPLIANCES, GASOLINE AND
OIL RESISTANT.

info@atlaswirecorp.com