Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

AX100540 Faceplates and Panels - FiberExpress Wall Mount Patch Panel - Medium Wall Mount

		For more Information please call 1-800-Belden1
General Description:	at Disale	
FiberExpress Patch Panel, Medium Wall Mou	пт, віаск.	
Usage (Overall)		
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main	Distribution Room
Related Parts:	FiberExpress Adapter Strips, Fiber Splice Organizer Trays and Kits	
Physical Characteristics (Connectivity)		
Capacity		
Max. Capacity:	4 Strips; 48 Fibers (SC, SCD, ST, FC); 96 Fibers (LCD, MT-RJ). Two 4 Two 12-inch splice tray kit (A0318904)	8-inch splice tray kit (A0649869),
Access		
Front Connection:	Flush	
Dimensions Dimensions:		
Height (in.) Width (in.) Depth (in.) 15.610 16.700 5.500		
Materials Materials: Description Material Panel Steel LH Door Steel RH Door Lexan Color		
Color:	Black	
Weight		
Weight:	11.570 lbs.	
Included Parts		
Included Parts:	6 Wood Screws (#10x1inch); 2 Velcro Strap; 9 Tie Wrap; 1 Admin Lab Manual	el; 1 Caution Label, 1 Installation
Packaging Packaging:	Individually packaged in a cardboard box.	
Mechanical Characteristics (Connectivity)		
Storage Temperature Range:	-40°C To +70°C	
Operating Temperature Range:	-10°C To +60°C	
Applicable Specifications and Agency Compliance (O Suitability	verall)	
Suitability - Indoor:	Yes	
Notes (Overall)		
Notes: For proper installation refer to Installation Guide PX101059 inc	cluded with the product or visit our web site at http://www.belden.com	
Product Family	· · ·	
Part Numbers:		
Description Item Number		
FiberExpress Wall Mount PP, Small, Black AX100495 FiberExpress Wall Mount PP, Medium, Black AX100540		
FiberExpress Wall Mount PP, Large, Black AX100540		

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX100540	1 EA	0.000 KG			FIBER EXPRESS WLMNT 24/48 BK



ENGLISH MEASUREMENT VERSION

AX100540 Faceplates and Panels - FiberExpress Wall Mount Patch Panel - Medium Wall Mount

Revision Date: 05-28-2009 Revision Number: 0

© 2015 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.