

SECURITY ALARM CABLE

UNSHIELDED

CMP/FT6 Rated, FPLP, CL2P, CL3P



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

PART NO.	AWG/ COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
			INCH	mm	INCH	mm	
22 AWG							
982202	22/2	SOL	.018	.457	.118	3.00	9
912202	22/2	7	.018	.457	.124	3.15	10
912203	22/3	7	.018	.457	.131	3.33	13
982204	22/4	SOL	.018	.457	.136	3.45	16
912204	22/4	7	.018	.457	.143	3.63	17
912206	22/6	7	.018	.457	.171	4.34	24
912208	22/8	7	.018	.457	.186	4.72	31
912210	22/10	7	.018	.457	.193	4.90	40
912212	22/12	7	.018	.457	.225	5.72	49
20 AWG							
912002	20/2	7	.018	.457	.138	3.51	14
912004	20/4	7	.018	.457	.160	4.06	24
18 AWG							
911802	18/2	7	.018	.457	.157	3.99	18
911803	18/3	7	.018	.457	.168	4.27	25
911804	18/4	7	.018	.457	.186	4.72	36
911805	18/5	7	.018	.457	.203	5.16	41
911806	18/6	7	.018	.457	.222	5.64	51
911808	18/8	7	.018	.457	.242	6.15	65
911809	18/9	7	.018	.457	.262	6.65	68
911810	18/10	7	.018	.457	.286	7.26	75
911812	18/12	7	.018	.457	.296	7.52	84
16 AWG							
911602	16/2	19	.018	.457	.180	4.57	26
911603	16/3	19	.018	.457	.191	4.85	38
911604	16/4	19	.018	.457	.211	5.36	52
14 AWG							
911402	14/2	19	.018	.457	.222	5.64	40
911403	14/3	19	.018	.457	.236	5.99	60
911404	14/4	19	.018	.457	.261	6.63	73
12 AWG							
911202	12/2	19	.018	.457	.272	6.91	58
911204	12/4	19	.018	.457	.308	7.82	111

PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, twisted with an overall low smoke white PVC jacket* with rip cord.

*Other colors available upon request. Please consult factory for minimums and lead times.

SPECIFICATIONS

Conductor	Bare Copper
Insulation	Low Smoke PVC
22 AWG	.007" PVC
20 AWG	.008" PVC
18 AWG	.009" PVC
16 AWG	.010" PVC
14-12 AWG	.012" PVC
Jacket	Low Smoke PVC
NEC Articles	
22-16 AWG:	FPLP/760, CMP/800, CL3P, CL2P/725
14-12 AWG:	FPLP, CL3P
Voltage Rating	300 V
Temp. Rating	75°C

APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

AVAILABLE PUT-UPS

1,000' Reels and Boxes
 500' Reels and Boxes
 Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

XX AWG XC (ETL)us TYPE CL3P/FPLP c(ETL)us
 TYPE CMP 3054355

*14-12 AWG are not recognized by c(UL) or c(ETL).

