

Aerospace Part#: TBD

CONTROL CABLE

DESCRIPTION

4 Conductors AWG 26/19x38 TPC
Foil Shielded 600V 200C White

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
4	26/19x38	Tinned Copper	FEP	.010"	.039"

Outer Shield Material

Drain Wire

Type	Material	Coverage	AWG	Material
Overall Foil Shield	Alum / Mylar	100%	26/7x34	Tinned Copper

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	White	.015"	.128" Nom.	2" Lay on Cable

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	11.6 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
Rated 600 Volts

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

MISCELLANEOUS

Color: White-Blue Stripe / White-Orange Stripe / White-Green Stripe / White
Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com



LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS

* Specification subject to error and may change without notice