
ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 534
Page 1 of 2 Pages


Issue: 4
Issue Date: 4/4/2006
Effective Date: 5/30/2006

A. Cordage Construction

- | | |
|-------------------------|--|
| 1) Conductor | |
| a) Material | Bare Copper, per ASTM B-3 |
| b) AWG, Stranding | 16 (65/34) AWG; Finer stranding may be used. |
| 2) Insulation | |
| a) Material | PVC |
| b) Nominal Diameter | 0.120 |
| 3) Core Assembly | |
| a) Number of Conductors | 3 |
| b) Color Code | Black, White & Green or Green/Yellow. The insulation colors are to be readily distinguishable from one another and consistent over their length and circumference.
<i>[Note: The stripe of the Green/Yellow insulation shall be 50% +/- 20%.]</i> |
| c) Fillers | Optional |
| d) Separator | Tissue Paper |
| 4) Jacket | |
| a) Material | PVC |
| b) Surface Finish | Smooth, non-striated |
| c) Nominal Diameter | 0.331 |
| d) Color | Black |
| e) UL, CSA Type | SJT |
| f) Jacket Marking | Per UL Standard 62 and CSA C22.2 No. 49. |

B. Cord Configuration

- | | |
|-------------------|---|
| 1) End 1 | Molded Vinyl Grounding Plug, NEMA 5-15P |
| 2) End 2 | Molded Vinyl Grounding Connector, IEC 320-C13 |
| 3) Mold Color | Black |
| 4) Overall Length | 118" +/- 2" |



Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 534
Page 2 of 2 Pages

Issue: 4
Issue Date: 4/4/2006
Effective Date: 5/30/2006

C. Industry Approvals and Ratings

- | | |
|-----------------------------------|---|
| 1) UL | UL Standard 62 & 817 |
| 2) CSA | CSA C22.2 No. 21 & No. 49 |
| 3) Cord Set Rating | 1625 Watts 13A-125V |
| 4) Temperature Rating | 60°C, Minimum |
| 5) EU Directive 2002/95/EC(RoHS): | All materials used in the manufacture and packaging of this part meet the requirement of EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. |
| 6) California Proposition 65: | The outer surface materials of this product are in accordance with CA Proposition 65 and contain no greater than 300 ppm of lead and meet all other chemical constraints as outlined in CA Proposition 65. |

D. Packaging

- | | |
|---------------------|----------------------------|
| 1) Standard Package | 25 Pieces, Hanked and Tied |
|---------------------|----------------------------|

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.