



ATLAS WIRE CORPORATION  
 9525 RIVER STREET  
 SCHILLER PARK, ILLINOIS 60176  
 (847) 678-1210  
 (847) 678-1281 FAX  
 www.atlaswirecorp.com



Atlas Wire Corporation  
 Registered to ISO9001 and TS16949  
 Schiller Park, IL 60176  
 Reference No. 10000854  
 Tucson, AZ 85714  
 Reference No. 10003647

MATERIAL SPECIFICATION SHEET

**#16 26/30 BC .016" PVC WITH .005" NYLON  
 RoHS COMPLIANT  
 MACHINE TOOL WIRE or TFFN 600v  
 GASOLINE AND OIL RESISTANT II  
 or AWM STYLE 1452 1000v or 1316/1408 600v or  
 CSA TEWN 105c-600v FT-1**

**CONDUCTOR:** #16 26/30 BC 1-1/4" LAY  
 APPROXIMATE NOMINAL O.D. .059"  
 APPROXIMATE CIRCULAR MILL AREA 2,600  
 WEIGHT PER THOUSAND FEET 8.10#  
 BASIC SPECIFICATION ASTM B 174

**PVC:** TEMPERATURE RATING 105c  
 VOLTAGE RATING 600v  
 ELONGATION 330%  
 SPECIFIC GRAVITY 1.35  
 DUROMETER DELAYED (SHORE) 92 (A)  
 TENSILE STRENGTH 2850 PSI  
 OXYGEN INDEX 29  
 BRITTLE POINT -25c

**NYLON:** ELONGATION 300%  
 SPECIFIC GRAVITY 1.13  
 TENSILE STRENGTH 11,500 PSI  
 OVERALL DIAMETER .101"  
 WEIGHT PER M FEET 11.03#  
 SPARK TESTED 10,000 VOLTS

**AWM USE:** INTERNAL WIRING OF APPLIANCES. GASOLINE AND OIL RESISTANT.