

Special Products

VSG Connection Splices for Flexible Conduits

- Use in railway vehicle construction and machine tooling
- High-grade formulated polyamide
- Self extinguishing
- Free from halogens and cadmium
- High pullout strength
- Fits fine (T) and coarse (G) conduit profiles



Cat. No. IP66	Cat. No. IP68	Fits to Conduit Size		Outside Diameter (mm)	Overall Length (mm)
		NW	Metric		
VSGD-1212GT	VSGR-1212	12	16	23.5	66.0
VSGD-1717GT	VSGR-1717	17	20	30.0	89.0
VSGD-2323GT	VSGR-2323	23	25	37.0	103.0
VSGD-2929GT	VSGR-2929	29	32	44.0	100.0
VSGD-3636GT	VSGR-3636	36	40	53.0	130.0
VSGD-4848GT	VSGR-4848	48	50	61.0	136.0

_ = Insert "B" to order black or "S" to order grey.

Temperature range: -40° C to 105° C;
Short term to 160° C

Content of delivery:

IP66: Connection splice with pre-installed universal safety clips (AFN2)

IP68: Connection splice with oval clips (OVN2), conduit seal (NVN3)

AV Conduit Adapters

- Use in connection with PMAFIX®/PMAFLEX® system
- High-grade, specially formulated polyamide 6
- Very high impact resistance
- Allows variable application of the PMAFIX® system, particularly of PMA® distribution pieces
- High conduit pullout strength
- Very good chemical properties
- Free from halogens and cadmium
- Fits fine (T) and coarse (G) conduit profiles



Cat. No. IP66, Black	Cat. No. IP68, Black	Fits to Conduit Size		Fits to Conduit Size		Overall Length (mm)
		NW	Metric	NW	Metric	
BAVD-10/07GT	BAVR-10/07	10	12	07	10	43.0
BAVD-12/10GT	BAVR-12/10	12	16	10	12	46.0
BAVD-17/10GT	BAVR-17/10	17	20	10	12	53.0
BAVD-17/12GT	BAVR-17/12	17	20	12	16	54.0
BAVD-23/10GT	BAVR-23/10	23	25	10	12	54.0
BAVD-23/12GT	BAVR-23/12	23	25	12	16	53.0
BAVD-23/17GT	BAVR-23/17	23	25	17	20	62.0
BAVD-29/10GT	BAVR-29/10	29	32	10	12	56.5
BAVD-29/12GT	BAVR-29/12	29	32	12	16	55.0
BAVD-29/17GT	BAVR-29/17	29	32	17	20	61.0
BAVD-29/23GT	BAVR-29/23	29	32	23	25	64.0
BAVD-36/29GT	BAVR-36/29	36	40	29	32	81.0
BAVD-48/36GT	BAVR-48/36	48	50	36	40	88.5

Temperature range: -40° C to 105° C;
Short term to 160° C

Content of delivery:

IP66: Adapter with pre-assembled universal safety clips (AFN2)

IP68: Adapter with oval clips (OVN2), conduit seal (NVN3)