

W-324-1

•REVISIONS•

REV	DESCRIPTION	ECN#
B	ADDED MAX/MIN DIMS.	2486



SPECIFICATIONS:

AWG: 28
 STRANDING: SOLID
 INSULATION TYPE: KYNAR (POLYVINYLIDENE FLUORIDE)
 COND. MATERIAL: COPPER CLAD STEEL
 PLATING: SILVER
 OUTER DIA: 0.0206" NOM.
 WALL THICKNESS: 0.004"
 OPERATING TEMP: 105°C UL
 MANUFACTURER: PMC
 MAN. P/N: SS374-RED
 V/T RATING: N/A
 INS. COLOR: **-1 RED**
 VENDOR: COLONIAL
 VENDOR P/N: KYNAR - 28 AWG - SPCCS - RED

BetaTHERM CORP. 910 TURNPIKE RD. SHREWBURY, MA. 01545				THE INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND MUST NOT BE DISCLOSED EXCEPT AS AUTHORIZED IN WRITING BY BETATHERM CORPORATION.		
TOL.	REVISIONS			LEAD WIRE		
	REV	DATE	BY			
DECIMAL +	A	initial	KC	DRAWN BY	SCALE	MATERIAL
	B	03/05/08	KC			
FRACTIONAL +	C			CHK'D	DATE	DRAWING NO.
	D					
ANGULAR +	E			TRACED	APP'D	W-324-1
	F					
				KC	NONE	
					11/01/2000	
					V.K.	