

# Certificate of Compliance

## Cable USA, Inc.

certify to all that, based upon certifications received from suppliers,  
the below listed Cable USA products meet the requirements of

### EU directive 2002/95EC (RoHS)

32300251




3/27/09

date

*[Handwritten Signature]*

signature







#704959

Scope: This drawing details a two-conductor 30 AWG shielded and jacketed high temperature cable. It is rated for 200°C and 300 volts maximum continuous use.

ITEM	DESCRIPTION	DIAMETER
Conductor:	Material: Tin Plated Copper Size: 30 AWG, 25 x 44	0.012" Nom.
Insulation:	Material: Extruded FEP Wall Thickness: .005" Nom.	0.022" Nom.
Color Code:	1. Black 2. White	
Cabling:	Two insulated conductors are cabled together Lay Length: 0.40" Nom.	0.044" Nom.
Shield:	Material: 44 AWG Tin Plated Copper Braid Coverage: 85% Min.	0.052" Nom.
Jacket:	Material: Extruded FEP Wall Thickness: .005" Nom. Color: Clear	0.062" Nom.
Specifications:	Working Temperature Range : -80°C to +200°C Voltage Rating : 300 Volts RMS	

REVISION # / APPROVED BY / DATE	DRAWN: Mark Osterhout 11/19/08	 A member of The Marmon Group of companies. 2584 South Horseshoe Drive Naples, FL, 34104-6195 Ph: 239-643-6400 Fx: 239-643-4230  ISO 9001-2000 Registration Number A4725
	CHECKED: <i>P. Blanchard</i> 11/19/08	
	APPROVED:	
THIS DRAWING IS THE PROPERTY OF CABLE USA, INC. AND ALL INFORMATION CONTAINED IS CONSIDERED PROPRIETARY. THIS DRAWING SHALL NOT BE COPIED OR ITS CONTENTS REVEALED TO THIRD PARTIES WITHOUT THE WRITTEN CONSENT OF CABLE USA, INC.		TITLE: 2/C 30 AWG SHIELDED CABLE, FEP/FEP 200°C, 300V - FINE WIRE
DRAWING NO. : 323002S1		PAGE 1 OF 1